

1


RH40C-ZID.GG.CR | 116154 | Portfolio STD-WW | Cpro ECblue

Technical Description

Motorized impeller RH..Cpro-ECblue

Standard design with ECblue motor and integrated electronics

Material of impeller:

- ZAmid - high performance composite material

Colour of impeller:

- Impeller colour RAL5002

Mains voltage motor size B_:

- 1~ 200...277 V; 50/60 Hz

Mains voltage motor size D_:

- 1~ 200...277 V; 50/60 Hz
- 3~ 200...240 V; 50/60 Hz
- 3~ 380...480 V; 50/60 Hz

Mains voltage motor size G_:

- 3~ 200...240 V; 50/60 Hz
- 3~ 380...480 V; 50/60 Hz

Thermal class:

- THCL155

Thermal protection:

- Protection with active temperature management

Protection:

- IP55

Coating:

- Motor painted in RAL5002

Controller (only motor size B_):

- Activation via external speed setting 0-10 V / PWM, Communication interface on request
- Standard cable length: 60 cm

Controller (only motor size D_, G_):

- BASIC: Activation via external speed setting 0-10 V / PWM Art. no. ER- and GR-module in basic version
- PREMIUM: Integrated control functionality, Communication interface

Cable glands:

- Motor size D: 3 x M16 x 1.5
- Motor size G: 3 x M20 x 1.5

Ambient temperature:

- Minimum permissible ambient temperature: -20 °C*
- Maximum permissible ambient temperature: 40 °C or see data sheet

***Continuous operation with occasional starts (S1) according to DIN EN 60034-1: 2011-02. Occasional starting between -35 ° C and -25 ° C is permissible. Permanent operation below -25 ° C only possible with special bearings for refrigeration applications on request.**



类型	RH40C-ZID.GG.CR
编号 article no.	116154 Portfolio STD-WW

技术参数

马达	ECblue
Efficiency class	IE5
主电源	- 3~ 400V 50Hz
环境温度 (t _r)	°C 40
效率 η_{statA}	% 61,8
效率 N_{实际} N_{目标}	64,4 62
ErP-等级	2015 内部集成EC控制器
grille influence	否


风机数据

风机速度 (n) max. (n _{max})	1/min - 3170
频率 (f_{BP}) (f _{max})	Hz 50 60
尺寸 (w x h x d)	mm 457 x 457 x 313
重量	kg 21
喷嘴压力系数 (k)	- 154


PF:PF_50; Type:RH40C-ZID.GG.CR; STol:+ -10 %

1 RH40C-ZID.GG.CR 根据ISO 5801 A型安装方式下在标准风筒下测试值
116154 | Portfolio STD-WW 测量密度 1.16 [kg/m³]


空气性能 p_{sf}



噪音值 ($L_{w(A),5}$)



噪音值 ($L_{w(A),6}$)






1 RH40C-ZID.GG.CR

f [Hz]	sum	63	125	250	500	1000	2000	4000	8000
$L_{w(A),5}$	-	-	-	-	-	-	-	-	-
$L_{w,5}$	-	-	-	-	-	-	-	-	-

f [Hz]	sum	63	125	250	500	1000	2000	4000	8000
$L_{w(A),6}$	-	-	-	-	-	-	-	-	-
$L_{w,6}$	-	-	-	-	-	-	-	-	-

- 1 **RH40C-ZID.GG.CR** 根据ISO 5801 A型安装方式下在标准风筒下测试值
116154 | Portfolio STD-WW 测量密度 1.16 [kg/m³]

 效率 $\eta_{F,sys}$

 效率 $\eta_{sF,sys}$

 功率 P_{sys}


1


RH40C-ZID.GG.CR

116154

3~ 380-480V 50Hz P1 5.60kW
 9.00-7.10A 3170/MIN 40°C
 3~ 380-480V 60Hz P1 5.60kW
 9.00-7.10A 3170/MIN 40°C
 IP55 THCL155

图纸


版本 FANselect V 1.01 (220310), AMCA V 1.03 September, 2021
 RLT V 1.00 Dezember, 2021 / 1.22.03.10 | 63849 | (用户 ZAFS53849)

2022-04-19

1


RH40C-ZID.GG.CR

116154


接线图

版本 FANselect V 1.01 (220310), AMCA V 1.03 September, 2021
 RLT V 1.00 Dezember, 2021 / 1.22.03.10 | 63849 | (用户 ZAFS53849)

2022-04-19

1


RH40C-ZID.GG.CR

116154

