


Technical data

Article number	122845
Type	RH56M-6DK.6K.1R
Designation	Single inlet impeller with backward curved blades.
Rated values	3~230/400V $\pm 10\%$ Δ/Y 50Hz P ₁ 0.63kW 2.50/ 1.45A $\Delta I=0\%$ 900/min COSY 0,63 70°C 3~265/460V $\pm 10\%$ Δ/Y 60Hz P ₁ 1.05kW 3.20/ 1.85A $\Delta I=5\%$ 1060/min COSY 0,72 70°C
Electrical connection	Supply cable axial, 9x 0,82mm ² (AWG18)x 85cm
Min. operating temperature [°C]	-40
Cable quality	Li7Y2G-J
Painting stator	_xx
coating rotor	_xx
Material impeller	Impeller made of aluminium
Painting impeller	unpainted
Connection diagram	1360-106XA
Rating plate	1x fixed.
Installation position	H/Vu/Vo
Motor protection	thermal contact
Type of protection	IP54
Thermal class	Thermal class 155
Impregnation	Moisture and hot climate protection
Balancing	6,3
Quality of bearings	ball bearing with long-time lubrication
Labelling UL/CSA	MK137-6DK.15.U
Certification	Motor-Recognized Component
Weight kg	22,30
ErP Data	Efficiency η_{statA} : 50.2 % Efficiency: $N_{actual} = 62.5 / N_{target} = 62^*$ *ErP 2015




Dimensions in mm
Shown drawing is just to show the dimensions of the fan.

1360-106XA

3~ motor with one speed and thermostatic switch (if built in).

U1	brown
V1	blue
W1	black
U2	red
V2	grey
W2	orange
TB	white

Δ-connection



Y-connection

