

# AC centrifugal fans

backward curved, Ø 133




- **Material:** Impeller: PA plastic 6.6, fibreglass-reinforced  
Rotor: Coated in black
- **Number of blades:** 7
- **Direction of rotation:** Clockwise, seen on rotor
- **Type of protection:** IP 22
- **Insulation class:** "B"
- **Mounting position:** Shaft horizontal or rotor on bottom; rotor on top on request
- **Condensate discharges:** Rotor-side
- **Mode of operation:** Continuous operation (S1)
- **Bearings:** Maintenance-free ball bearings

Nominal data		Curve	Nominal voltage	Frequency	Air flow	Speed/rpm	Power input	Current draw	Capacitor	Sound pressure level	Perm. amb. temp.	Electr. connection
Type	Motor	VAC	Hz	m³/h	rpm	W	A	µF/VDB	dB(A)	°C	p. 596 f.	
R2S 133	M2S 052-CA	Ⓐ 1~ 230	50	280	2780	36	0.25	—	55	-25 to +40	B)	
		1~ 230	60	320	3200	34	0.21	—	58	-25 to +60		

subject to alterations

## Curves



- **Motor protection:** TOP wired internally
- **Cable exit:** Axial
- **Protection class:** I
- **Product conforming to standards:** EN 60335-1, CE
- **Approvals:** CCC



Mass of centrifugal fan



Centrifugal fan	kg	Inlet nozzle (long)
R2S 133-AE17 -05	0.9	09566-2-4013

