

A3G560-AP68-35

EC axial fan - HyBlade®

sickled blades (S series)

for agricultural ventilation

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

County court Stuttgart · HRB 590142



Nominal data

Type	A3G560-AP68-35	
Motor	M3G112-EA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Type of data definition		ml
Speed	min ⁻¹	1000
Power input	W	400
Current draw	A	1.8
Max. back pressure	Pa	100
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.00

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	41.1	27.2	31.2
Efficiency grade N		49.9	36	40
Power input P_{ed}	kW	0.4		
Air flow q_v	m ³ /h	5245		
Pressure increase p_{fs}	Pa	102		
Speed n	min ⁻¹	995		

Data definition with optimum efficiency.

The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

LU-118048



A3G560-AP68-35

EC axial fan - HyBlade®

sickled blades (S series)

for agricultural ventilation

Technical features

Mass	8.8 kg
Size	560 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium, coated in black
Material of blades	Aluminium sheet insert (coated in black), sprayed with PP plastic
Number of blades	5
Blade angle	-5°
Direction of air flow	"A"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"B"
Humidity class	F4-2
Max. permissible ambient motor temp. (transp./ storage)	80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on top
Condensate discharge holes	On the stator side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - Alarm relay - Integrated PID controller - Motor current limit - PFC, active - RS485 ebmBUS - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 55022 (Class A, industrial environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) wired internally
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	EAC


A3G560-AP68-35

EC axial fan - HyBlade®

sickled blades (S series)

for agricultural ventilation

Product drawing



1	Direction of air flow "A"
2	Cable diameter: min. 4 mm, max. 10 mm; tightening torque: 2.5±0.4 Nm
3	Depth of screw 12 - 16 mm
4	Tightening torque 3.5±0.5 Nm

A3G560-AP68-35

EC axial fan - HyBlade®

sickled blades (S series)

for agricultural ventilation

Connection screen

KL3										KL2			KL1							
RS A	RS B	RS A	RS B	GND	0-10 V PWM	4-20 mA	+20 V	+10 V	0-10 V PWM	GND	OUT	NO	COM	NC		L		N		PE

No.	Conn.	Designation	Function / assignment
PE		PE	Protective earth
KL1		N	Mains 50/60 Hz, neutral
KL1		L	Mains 50/60 Hz, phase
KL2		COM	Alarm relay, COMMON (2A, 250 VAC, AC1)
KL2		NC	Alarm relay, normally closed connection
KL2		NO	Alarm relay, close with error
KL3		+10 V	Supply for external potentiometer, 10 VDC (+10%) @ 10 mA
KL3		+20 V	Supply for external sensor, 20 VDC (±20%) @ 50 mA
KL3		0-10 V/PWM	Control / Actual sensor value input
KL3		0-10 V/PWM	Control / Actual sensor value input (impedance 100 kΩ)
KL3		4-20 mA	Control / Actual sensor value input
KL3		GND	GND
KL3		GND	GND
KL3		OUT	Master output 0-10 V max. 3 mA
KL3		RSA	RS485 interface for ebmBUS; RS A
KL3		RSA	RS485 interface for ebmBUS; RS A
KL3		RSB	RS485 interface for ebmBUS; RS B
KL3		RSB	RS485 interface for ebmBUS; RS B


A3G560-AP68-35

EC axial fan - HyBlade®

sickled blades (S series)

for agricultural ventilation

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa
1	230	50	1000	293	1.29	60	67	67	8360	0
2	230	50	1000	336	1.48	59	66	66	7500	35
3	230	50	1000	369	1.61	60	67	66	6460	70
4	230	50	1000	400	1.80	62	69	68	5400	100
5	230	50	850	182	0.80	57	64	64	7130	0
6	230	50	850	209	0.92	56	63	62	6405	26
7	230	50	850	231	1.01	57	63	62	5530	51
8	230	50	850	249	1.09	59	65	65	4620	73
9	230	50	700	102	0.45	53	59	59	5870	0
10	230	50	700	117	0.51	52	58	58	5275	17
11	230	50	700	129	0.57	52	59	58	4550	35
12	230	50	700	139	0.61	55	61	61	3805	50
13	230	50	550	49	0.22	47	54	54	4610	0
14	230	50	550	57	0.25	46	53	53	4145	11
15	230	50	550	63	0.27	47	54	53	3575	21
16	230	50	550	68	0.30	49	56	55	2990	31

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
qv = Air flow · p_{fs} = Pressure increase