

R2E190-RA26-22

# AC centrifugal fan - RadiCal

backward-curved, single-intake



**ebm-papst Mulfingen GmbH & Co. KG**  
Bachmühle 2 · D-74673 Mulfingen  
Phone +49 7938 81-0  
Fax +49 7938 81-110  
info1@de.ebmpapst.com  
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen  
Amtsgericht (court of registration) Stuttgart · HRA 590344  
General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen  
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data


|                             |                   |         |         |
|-----------------------------|-------------------|---------|---------|
| Type                        | R2E190-RA26-22    |         |         |
| Motor                       | M2E068-BF         |         |         |
| Phase                       |                   | 1~      | 1~      |
| Nominal voltage             | VAC               | 230     | 230     |
| Frequency                   | Hz                | 50      | 60      |
| Method of obtaining data    |                   | ml      | ml      |
| Valid for approval/standard |                   | CE      | CE      |
| Speed (rpm)                 | min <sup>-1</sup> | 2350    | 2500    |
| Power consumption           | W                 | 52      | 65      |
| Current draw                | A                 | 0.23    | 0.29    |
| Capacitor                   | µF                | 1.5     | 1.5     |
| Capacitor voltage           | VDB               | 400     | 400     |
| Capacitor standard          |                   | S0 (CE) | S0 (CE) |
| Min. back pressure          | Pa                | 0       | 0       |
| Min. back pressure          | in. wg            | 0       | 0       |
| Min. ambient temperature    | °C                | -25     | -25     |
| Max. ambient temperature    | °C                | 65      | 75      |
| Starting current            | A                 | 0.37    | 0.37    |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

## Technical description


|                                                                            |                                                                    |
|----------------------------------------------------------------------------|--------------------------------------------------------------------|
| Weight                                                                     | 1.2 kg                                                             |
| Size                                                                       | 190 mm                                                             |
| Motor size                                                                 | 68                                                                 |
| Rotor surface                                                              | Painted black                                                      |
| Impeller material                                                          | PA plastic                                                         |
| Number of blades                                                           | 7                                                                  |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                     |
| Degree of protection                                                       | IP44; installation- and position-dependent as per EN 60034-5       |
| Insulation class                                                           | "B"                                                                |
| Moisture (F) / Environmental (H) protection class                          | H1                                                                 |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                            |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                            |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request       |
| Condensation drainage holes                                                | On rotor side                                                      |
| Mode                                                                       | S1                                                                 |
| Motor bearing                                                              | Ball bearing                                                       |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                          |
| Motor protection                                                           | Temperature limiter manual reset; Temperature limiter manual reset |
| With cable                                                                 | Variable                                                           |
| Protection class                                                           | I (with customer connection of protective earth)                   |
| Conformity with standards                                                  | EN 60335-1; CE                                                     |

Product drawing




|   |                                                                           |
|---|---------------------------------------------------------------------------|
| 1 | Accessory part: inlet ring 09576-2-4013 not included in scope of delivery |
| 2 | Max. clearance for screw 5 mm                                             |
| 3 | Cable PVC 4G 0.5 mm², 4x crimped splices                                  |

Connection diagram



|    |              |   |       |    |       |
|----|--------------|---|-------|----|-------|
| U1 | blue         | Z | brown | U2 | black |
| PE | green/yellow |   |       |    |       |

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-125749-1


Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|----------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | m³/h           | Pa              | cfm            | in. wg          |
| 1 | 230 | 50 | 2490              | 47             | 0.21 | 58                | 66                | 540            | 0               | 320            | 0.00            |
| 2 | 230 | 50 | 2440              | 50             | 0.22 | 55                | 63                | 445            | 100             | 260            | 0.40            |
| 3 | 230 | 50 | 2350              | 52             | 0.23 | 52                | 60                | 305            | 180             | 180            | 0.72            |
| 4 | 230 | 50 | 2450              | 49             | 0.22 | 55                | 62                | 180            | 240             | 105            | 0.96            |

U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-125753-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|----------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | m³/h           | Pa              | cfm            | in. wg          |
| 1 | 230 | 60 | 2715              | 60             | 0.26 | 60                | 68                | 590            | 0               | 345            | 0.00            |
| 2 | 230 | 60 | 2630              | 62             | 0.27 | 58                | 65                | 470            | 120             | 280            | 0.48            |
| 3 | 230 | 60 | 2500              | 65             | 0.29 | 54                | 61                | 295            | 220             | 175            | 0.88            |
| 4 | 230 | 60 | 2705              | 60             | 0.27 | 59                | 66                | 170            | 300             | 100            | 1.20            |

U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase