

W2E200-CH38-01

# AC axial fan

sickle-shaped blades (S series)  
with round full nozzle



**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                             |                   |      |      |
|-----------------------------|-------------------|------|------|
| Type                        | W2E200-CH38-01    |      |      |
| Motor                       | M2E068-BF         |      |      |
| Phase                       |                   | 1~   | 1~   |
| Nominal voltage             | VAC               | 230  | 230  |
| Frequency                   | Hz                | 50   | 60   |
| Method of obtaining data    |                   | fa   | fa   |
| Valid for approval/standard |                   | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup> | 2600 | 2900 |
| Power consumption           | W                 | 64   | 78   |
| Current draw                | A                 | 0.3  | 0.34 |
| Capacitor                   | µF                | 1.5  | 1.5  |
| Capacitor voltage           | VDB               | 450  | 450  |
| Max. back pressure          | Pa                | 150  | 150  |
| Max. back pressure          | in. wg            | 0.6  | 0.6  |
| Min. ambient temperature    | °C                | -25  | -25  |
| Max. ambient temperature    | °C                | 65   | 65   |
| Starting current            | A                 | 0.55 | 0.54 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

# AC axial fan

sickle-shaped blades (S series)

with round full nozzle


## Technical description

|                                                                            |                                                              |
|----------------------------------------------------------------------------|--------------------------------------------------------------|
| Weight                                                                     | 2.32 kg                                                      |
| Fan size                                                                   | 200 mm                                                       |
| Rotor surface                                                              | Painted black                                                |
| Blade material                                                             | Sheet steel, painted black                                   |
| Fan housing material                                                       | Sheet steel, pre-galvanized and coated with black plastic    |
| Guard grille material                                                      | Steel, phosphated and coated with black plastic              |
| Number of blades                                                           | 9                                                            |
| Airflow direction                                                          | "V"                                                          |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                        |
| Degree of protection                                                       | IP44                                                         |
| Insulation class                                                           | "B"                                                          |
| Moisture (F) / Environmental (H) protection class                          | H1                                                           |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                      |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                      |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes                                                | On rotor side                                                |
| Mode                                                                       | S1                                                           |
| Motor bearing                                                              | Ball bearing                                                 |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                    |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected        |
| With cable                                                                 | Variable                                                     |
| Protection class                                                           | I (with customer connection of protective earth)             |
| Conformity with standards                                                  | EN 60335-1; CE                                               |
| Approval                                                                   | CCC                                                          |

# AC axial fan


sickle-shaped blades (S series)  
with round full nozzle

## Product drawing



- |   |                                          |
|---|------------------------------------------|
| 1 | Direction of air flow "V"                |
| 2 | Cable PVC 4G 0.5 mm², 4x crimped splices |

## Connection diagram




- |    |              |   |       |    |       |
|----|--------------|---|-------|----|-------|
| U1 | blue         | Z | brown | U2 | black |
| PE | green/yellow |   |       |    |       |

# AC axial fan

sickle-shaped blades (S series)  
with round full nozzle

## Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-26449-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | cfm            | in. wg          |
| 1 | 230 | 50 | 2600              | 64             | 0.30 | 915            | 0               | 535            | 0.00            |
| 2 | 230 | 50 | 2560              | 66             | 0.30 | 830            | 30              | 485            | 0.12            |
| 3 | 230 | 50 | 2500              | 69             | 0.31 | 715            | 60              | 420            | 0.24            |
| 4 | 230 | 50 | 2465              | 70             | 0.32 | 595            | 80              | 350            | 0.32            |


U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

## AC axial fan

sickle-shaped blades (S series)

with round full nozzle

**Curves: Air performance 60 Hz**


$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-26450-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>V</sub>    | p <sub>fs</sub> | q <sub>V</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1 | 230 | 60 | 2900              | 78             | 0.34 | 1025              | 0               | 600            | 0.00            |
| 2 | 230 | 60 | 2845              | 80             | 0.35 | 940               | 30              | 555            | 0.12            |
| 3 | 230 | 60 | 2745              | 84             | 0.36 | 830               | 60              | 490            | 0.24            |
| 4 | 230 | 60 | 2665              | 87             | 0.37 | 650               | 90              | 385            | 0.36            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>is</sub> = Pressure increase

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ebm-papst:](#)

[W2E200-CH38-01](#)