



"C17BF" SERIES COSTECH FANS

Description: Axial fan a.c. 172X150x38mm



- Casing material:** Black varnished aluminium
Impeller material: Black fibreglass reinforced plastic (PBT PC) UL 94V-0
Protection degree: IP20, according to EN 60529 standard
Fixing system: by No 4 M4 screws
Motor protection: thermal
Storage temperature: from -40°C to +80°C
Rated temperature range: from -40°C to +70°C
Lifetime L10 at 40°C: 40,000 h
Electrical connection: flat terminals 110 series (2.8x0.5 mm)
Approvals: UL E223195
Weight: 0,72 kg



Model	Bearing	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Noise	RPM	Approvals
		(V)	(Hz)	(A)	(W)	(m3/h)	(Pa)	[db(A)]	(rpm)	
C17B12HTBF00	Ball	115 V a.c.	50/60	0.250/0.230	29/28	300/360	167/187	54.0/58.0	2,850/3,400	CE; cURus
C17B23HTBF00	Ball	230 V a.c.	50/60	0.110/0.110	27/26	300/360	167/187	54.0/58.0	2,850/3,400	CE; cURus

All specifications, data and drawing are subject to change without notice and are approximate. Please refer to our terms of sales including our warranty and limited liabilities clauses.