



CLG-L series LED lamps

- Long life and low energy consumption by LED technology
- ON/OFF switch
- Metal fixing brackets for an adjustable lamp positioning
- Daisy chain connection

Model	Length	Rated Voltage	Rated power	No. of led	Color Temp.	Approvals
	mm	V	W		K	
CLG-L307	400	115-230V a.c.	7	12	6,400	CE;



CLG series fluorescent lamps

- Equipped with fluorescent lamp type: T5 with lamp holder G5 type for CLG-R models; T4 with lamp holder G5 type for CLG-T models; T8 with lamp holder G13 type for CLG-S models
- ON/OFF switch
- Magnetic mounting system for CLG-T models available
- Schuko socket version (CLG-SS)

Model	Length	Rated Voltage	Rated power	Light type lamp holder	Cable length	Approvals
	mm	V	W		mm	
CLG-R2313	581	230 V a.c.	13	T5 / G5	1,800	CE;
CLG-R2321	914	230 V a.c.	21	T5 / G5	1,800	CE;
CLG-R236	277	230 V a.c.	6	T5 / G5	1,300	CE; GS;
CLG-R238	354	230 V a.c.	8	T5 / G5	1,800	CE;
CLG-SS2310	498	230 V a.c.	10	T8 / G13	-	CE;
CLG-T2312	425	230 V a.c.	12	T4 / G5	1,800	CE; GS;
CLG-T2316	516	230 V a.c.	16	T4 / G5	1,800	CE;
CLG-T2320	616	230 V a.c.	20	T4 / G5	1,800	CE;
CLG-T2324	710	230 V a.c.	24	T4 / G5	1,800	CE;
CLG-T2330	810	230 V a.c.	30	T4 / G5	1,800	CE;
CLG-T236	270	230 V a.c.	6	T4 / G5	1,800	CE; GS;
CLG-T238	390	230 V a.c.	8	T4 / G5	1,800	CE; GS;

Accessories for Fluorescent lamps

Model	Descriptions
CONNECTION CABLE	
CVL01-200	multiple connection cable 2000 mm
CVL01-25	multiple connection cable 250 mm
CVL02-150	multiple connection cable 1500 mm
CVL02-200	connection cable 2000 mm
CVL02-350	connection cable 3500 mm
MAGNETIC SUPPORT	
CLG-TSM1	for CLG-T models