

"TP19_IP44" SERIES

Description: **Roof Exhaust Unit IP44**



- Type or material:

Standard colour:

Protection degree:

Fixing method:

Plate thickness:

Storage temperature:

Motor Lifetime L10 at 25°C

80%RH (approx.):

Working class of capacitor:

Motor protection:

Electrical connection:

Earth connection:

Appliance class:

Weight:

Approvals:
- ABS/PC alloy and aluminium

RAL 7035 - other colours on request

IP44, according to EN 60529 standard

By No 8 Ø4x16 mm screws for thermoplastic material

any

from -20°C to +60°C

115V 75,000h 50Hz; 80,000h 60Hz

230V 59,000h 50Hz; 73,000h 60Hz

class B

thermal

by terminal block 3 poles L-N-PE


(by terminal block, PE pole)

class I



2.1 Kg

CE

technical drawing



mounting cut-out



Model	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Fan Noise	Rated Temp. Range	Approvals
	(V)	(Hz)	(A)	(W)	(m3/h)	(Pa)	[db(A)]	(°C)	
TP19U230B44	230 V a.c.	50/60	0.309/0.354	69/81	485/560	330/470	67.9/71.0	-10 - +60	CE

data with uncertainty of 10%

All specifications, data and drawing are subject to change without notice and are approximate. Please refer to our terms of sales including our warranty and limited liabilities clauses.