

#1 DATA SHEET


R09P-3530HA-4M-4237



Stamped Steel Blades with guard grill and wall plate long inlet



Ordering code: 0309-4-1013

Operating Point		Nominal data		Erp Data	
Air flow [m3/h]	1975	Phase [~]	1	Overall efficiency [%]	29.0
Static pressure [Pa]	64	Voltage [V]	230 / 230	Measurement cat.	A
Density [kg/m3]	1.2	Voltage range [V]	N / A	Efficiency category	static
Total pressure [Pa]	83	Frequency [Hz]	50 / 60	Efficiency grade N	40.7
Rotation speed [1/min]	1295	Input power [W]	130 / 165	Variable speed drive	NO
Input power [W]	146	Input current [A]	0.6 / 0.72	Power input [kW]	0.14
Current [A]	0.66	Nominal speed [rpm]	1290 / 1380	Airflow [m3/h]	1975
Total efficiency [%]	31	Min. ambient temp. [°C]	-30	Pressure drop [Pa]	79
Static efficiency [%]	24	Max. ambient temp. [°C]	60	Rotational Speed [rpm]	1333
Sound power [dB]	0	Protection class	IP54	Specific ratio	1.00
Weighted sound power [dB(A)]	0	Insulation class	155		
Sound pressure [dB]	0	Capacitor [μF/450V]	4.00		
Weighted sound pressure [dB(A)]	0	K. Value	N / A		
		Connection	N / A		
		Weight [Kg]	6.2		


Static pressure







Specific fan power



Overall static efficiency

