

R09R-3130HA-4T-3524

Stamped Steel Blades with guard grill for short inlet

Ordering code: 0309-4-1039

Operating Point		Nominal data		Erp Data (This fan is not subject to the EU ErP regulation)	
Air flow [m ³ /h]	1379	Phase [~]	3	Overall efficiency [%]	N/A
Static pressure [Pa]	60	Voltage [V]	400 / 400 / 230 / 230	Measurement cat.	N/A
Density [kg/m ³]	1.2	Voltage range [V]	N / A	Efficiency category	N/A
Total pressure [Pa]	75	Frequency [Hz]	50 / 60 / 50 / 60	Efficiency grade N	N/A
Rotation speed [1/min]	1338	Input power [W]	100 / 120 / 100 / 120	Variable speed drive	N/A
Input power [W]	117	Input current [A]	0.23 / 0.22 / 0.41 / 0.39	Power input [kW]	N/A
Current [A]	0.28	Nominal speed [rpm]	1340 / 1490 / 1340 / 1490	Airflow [m ³ /h]	N/A
Total efficiency [%]	24	Min. ambient temp. [°C]	-30	Pressure drop [Pa]	N/A
Static efficiency [%]	20	Max. ambient temp. [°C]	55	Rotational Speed [rpm]	N/A
Sound power [dB]	0	Protection class	IP54	Specific ratio	N/A
Weighted sound power [dB(A)]	0	Insulation class	155		
Sound pressure [dB]	0	Capacitor [μF/450V]	N / A		
Weighted sound pressure [dB(A)]	0	K. Value	N / A		
		Connection	Y / Y / D / D		
		Weight [kg]	3.4		

Static pressure









