


R09R-36LPS-6M-4249

Plastic Blades with guard grill for short inlet


Ordering code: 0309-4-0436

Operating Point		Nominal data		Erp Data (This fan is not subject to the EU ErP regulation)	
Air flow [m3/h]	1188	Phase [~]	1	Overall efficiency [%]	N/A
Static pressure [Pa]	26	Voltage [V]	230 / 230	Measurement cat.	N/A
Density [kg/m3]	1.2	Voltage range [V]	N / A	Efficiency category	N/A
Total pressure [Pa]	33	Frequency [Hz]	50 / 60	Efficiency grade N	N/A
Rotation speed [1/min]	793	Input power [W]	65 / 70	Variable speed drive	N/A
Input power [W]	73	Input current [A]	0.30 / 0.32	Power input [kW]	N/A
Current [A]	0.34	Nominal speed [rpm]	830 / 900	Airflow [m3/h]	N/A
Total efficiency [%]	15	Min. ambient temp. [°C]	-30	Pressure drop [Pa]	N/A
Static efficiency [%]	12	Max. ambient temp. [°C]	60	Rotational Speed [rpm]	N/A
Sound power [dB]	0	Protection class	IP54	Specific ratio	N/A
Weighted sound power [dB(A)]	0	Insulation class	155		
Sound pressure [dB]	0	Capacitor [μF/450V]	1.50		
Weighted sound pressure [dB(A)]	0	K. Value	N / A		
		Connection	N / A		
		Weight [Kg]	3.8		

Static pressure



Total pressure



Input power

