


R13E-5030HA-4M-7075

Stamped Aluminium Blades with


Ordering code: 0313-4-1121

Operating Point		Nominal data		Erp Data	
Air flow [m ³ /h]	6828	Phase [~]	1	Overall efficiency [%]	29.4
Static pressure [Pa]	121	Voltage [V]	230	Measurement cat.	A
Density [kg/m ³]	1.2	Voltage range [V]	N / A	Efficiency category	static
Total pressure [Pa]	177	Frequency [Hz]	50	Efficiency grade N	36.4
Rotation speed [1/min]	1331	Input power [W]	780	Variable speed drive	NO
Input power [W]	777	Input current [A]	3.5	Power input [kW]	0.77
Current [A]	3.51	Nominal speed [rpm]	1370	Airflow [m ³ /h]	6828
Total efficiency [%]	43	Min. ambient temp. [°C]	-30	Pressure drop [Pa]	124
Static efficiency [%]	30	Max. ambient temp. [°C]	60	Rotational Speed [rpm]	1336
Sound power [dB]	0	Protection class	IP54	Specific ratio	1.00
Weighted sound power [dB(A)]	0	Insulation class	155		
Sound pressure [dB]	0	Capacitor [μF/450V]	16.00		
Weighted sound pressure [dB(A)]	0	K. Value	N / A		
		Connection	N / A		
		Weight [Kg]	10.7		


Static pressure





Total pressure




Input power





Specific fan power



Overall static efficiency

