

■ B8 (50Hz 380-415V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	50Hz						Заправка маслом	Примечание
				Производительность		Мощность двигателя	Ток	COP			
	л.с.	см3/оборот	кВт	кBTU/h	кВт	A	W/W	BTU/Wh	Liter		
3Ph	4	66.8	3CB067SA0M	8.00	27.3	3.25	6.1	2.46	8.4	1.7	
	5	84.4	3CB084SA0M	10.00	34.1	4.00	7.2	2.50	8.5	1.7	
	6	100.0	3CB100SA0M	11.80	40.3	4.80	8.3	2.46	8.4	1.7	
	7	110.2	3CB110SA0M	13.00	44.4	5.25	9.4	2.48	8.4	1.7	
	8	137.0	3CC137LA0M	16.05	54.8	6.70	11.9	2.40	8.2	2.8	
	9	148.8	3CC149LA0M	17.40	59.4	7.20	12.6	2.42	8.2	2.8	
	10	171.2	3CC171LA0M	19.85	67.7	8.10	14.2	2.45	8.4	2.8	
	12	205.4	3CC205LA0M	23.00	78.5	9.70	16.6	2.37	8.1	2.8	