

■ B8 (50Hz 380-415V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
	л.с.	см3/оборот	кВт	кBTU/h	кВт	A	W/W			BTU/Wh	Liter		
3Ph	3.1	51.8	C-SB263H8B	809 831 88	—	9.2	31.2	3.0	5.5	3.10	10.6	1.7	
			C-SB263H8C	809 832 88	—	9.2	31.2	3.0	5.5	3.10	10.6	1.7	
	3.5	55.7	C-SB263H8A	809 830 88	—	9.6	32.8	3.1	5.7	3.10	10.6	1.7	
			C-SBX120H38A	—	—	10.0	34.1	3.0	5.7	3.33	11.4	1.7	
	4	66.8	C-SB303H8A	809 840 88	—	11.8	40.3	3.7	6.5	3.23	11.0	1.7	
			C-SB303H8G	809 846 88	—	11.8	40.3	3.7	6.5	3.23	11.0	1.7	Тандем
			C-SBX145H38A	—	—	12.0	40.9	3.6	6.5	3.38	11.5	1.7	
	4.2	70.5	C-SBX150H38C	—	—	12.8	43.7	3.7	6.5	3.51	12.0	1.4	
		70.9	C-SBX150H38A	—	—	12.8	43.7	3.8	6.7	3.41	11.6	1.7	
	4.4	73.2	C-SBX160H38A	—	—	13.1	44.7	3.9	7.0	3.40	11.6	1.4	
	4.5	76.0	C-SBX165H38A	809 745 88	—	13.5	46.1	4.1	7.2	3.33	11.4	1.7	
			C-SBX165H38B	809 746 88	—	13.5	46.1	4.1	7.2	3.33	11.4	1.7	Тандем
			C-SBX165H38C	—	—	13.6	46.4	4.1	7.3	3.32	11.3	1.7	
	4.6	77.4	C-SB353H8A	809 842 88	—	13.5	46.1	4.3	7.5	3.18	10.8	1.7	
			C-SB353H8G	809 847 88	—	13.5	46.1	4.3	7.5	3.18	10.8	1.7	Тандем
	4.9	81.0	C-SBX180H38A	809 750 88	—	14.3	48.8	4.3	7.6	3.33	11.3	1.7	
			C-SBX180H38B	809 751 88	—	14.3	48.8	4.3	7.6	3.33	11.3	1.7	Тандем
	5	83.2	C-SB373H8A	809 850 88	—	14.5	49.5	4.5	7.9	3.19	10.9	1.7	
			C-SB373H8G	809 856 88	—	14.5	49.5	4.5	7.9	3.19	10.9	1.7	Тандем
		83.7	C-SBX180H38C	809 753 88	—	14.7	50.2	4.5	7.7	3.30	11.3	1.7	
			C-SBX180H38D	809 754 88	—	14.7	50.2	4.5	7.7	3.30	11.3	1.7	Тандем
	5.2	85.5	C-SB373H8F	809 855 88	—	15.0	51.2	4.7	8.1	3.19	10.9	1.7	
	5.5	90.6	C-SBX195H38A	—	—	16.3	55.6	4.9	8.9	3.33	11.4	1.7	
			C-SBR195H38A	—	—	16.0	54.6	5.0	8.4	3.20	10.9	1.7	
	6	100.0	C-SBX215H38P	—	—	17.8	60.7	5.4	9.4	3.33	11.4	1.7	
			C-SB453H8A	809 860 88	—	17.7	60.4	5.4	9.3	3.26	11.1	1.7	
			C-SB453H8G	809 866 88	—	17.7	60.4	5.4	9.3	3.26	11.1	1.7	Тандем
	7	110.2	C-SBR235H38A	—	—	19.2	65.5	6.0	10.7	3.20	10.9	1.7	
			C-SBR235H38B	—	—	19.2	65.5	6.0	10.7	3.20	10.9	1.7	Тандем
	7.7	131.9	C-SC583H8H	809 284 88	—	23.6	80.5	7.2	12.3	3.30	11.3	2.8	
			C-SC583H8K	809 286 88	—	23.6	80.5	7.2	12.3	3.30	11.3	2.8	Тандем
	8	137.0	C-SC603H8H	809 281 88	—	24.5	83.6	7.4	12.6	3.31	11.3	2.8	
			C-SC603H8K	809 283 88	—	24.5	83.6	7.4	12.6	3.31	11.3	2.8	Тандем
	9	148.8	C-SC673H8H	809 291 88	—	26.5	90.4	8.1	13.6	3.29	11.2	2.8	
			C-SC673H8K	809 293 88	—	26.5	90.4	8.1	13.6	3.29	11.2	2.8	Тандем
	10	171.2	C-SC753H8H	809 201 88	—	30.6	104.4	9.1	15.4	3.38	11.5	2.8	
			C-SC753H8K	809 203 88	—	30.6	104.4	9.1	15.4	3.38	11.5	2.8	Тандем
			C-SC753H8T	809 205 88	—	30.6	104.4	9.1	15.4	3.38	11.5	2.8	смотровое стекло
	11.4	194.9	C-SCX435H38B	—	—	36.1	123.2	10.4	18.9	3.47	11.8	2.8	Тандем
	11.6	199.1	C-SC863H8H	809 224 88	—	35.2	120.1	10.6	17.7	3.32	11.3	2.8	
	12	205.4	C-SC903H8H	809 221 88	—	36.1	123.2	10.9	18.2	3.31	11.3	2.8	
			C-SC903H8K	809 223 88	—	36.1	123.2	10.9	18.2	3.31	11.3	2.8	Тандем
			C-SC903H8T	809 225 88	—	36.1	123.2	10.9	18.2	3.31	11.3	2.8	смотровое стекл

■ B5 (50Hz 220-240V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
						кВт	кBTU/h			W/W	BTU/Wh		
1Ph	3.1	51.8	C-SBR110H15A	—	PSC	9.10	31.1	3.1	14.6	2.94	10.0	1.7	
	3.5	55.7	C-SBR120H15A	—	PSC	9.70	33.1	3.3	15.0	2.98	10.2	1.7	
			C-SBR120H15P	—	PSC	9.70	33.1	3.3	15.4	2.98	10.2	1.7	T3
	3.6	60.4	C-SBX135H15A	—	CSR	11.0	37.5	3.3	15.1	3.33	11.4	1.4	
	4	66.8	C-SBX145H15A	—	CSR	12.0	40.9	3.6	16.7	3.33	11.4	1.4	
			C-SBR145H15A	—	PSC	11.7	39.9	3.8	17.4	3.12	10.6	1.7	
			C-SBR145H15P	—	PSC	11.8	40.3	3.7	17.0	3.19	10.9	1.4	T3
	4.6	77.4	C-SBR165H15A	—	PSC	13.7	46.7	4.5	20.3	3.08	10.5	1.4	
5	83.2	C-SBR180H15A	—	PSC	14.8	50.5	4.8	22.3	3.08	10.5	1.4		
5.8	93.1	C-SBR200H15H	—	PSC	16.4	56.0	5.3	24.2	3.12	10.7	1.7		
3Ph	4	66.8	C-SB303H5A	809 840 85	—	11.7	39.9	3.7	12.4	3.16	10.8	1.7	
	5	83.2	C-SB373H5A	809 850 85	—	14.7	50.2	4.7	13.9	3.16	10.8	1.7	
	6	100.0	C-SB453H5A	809 860 85	—	17.8	60.7	5.5	16.8	3.24	11.0	1.7	
	8	137.0	C-SC603H5H	809 281 85	—	24.2	82.6	7.4	22.2	3.29	11.2	2.8	
	10	171.2	C-SC753H5H	809 201 85	—	30.6	104.4	9.1	27.2	3.36	11.5	2.8	
	12	205.4	C-SC903H5H	809 221 85	—	36.0	122.8	10.9	32.1	3.30	11.3	2.8	

эратура кипения 7.2°C, Переохладение 8.3K, Перегрев 11.1K