

Спиральные компрессоры для кондиционирования

R410A 50Hz

■ B8 (50Hz 380-415V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
						кВт	кBTU/h			кВт	A	W/W	
3Ph	3.5	39.9	C-SBP120H38A	—	—	10.0	34.1	3.50	6.4	2.86	9.7	1.7	
			C-SBP120H38B	—	—	10.0	34.1	3.50	6.4	2.86	9.7	1.7	Тандем
			C-SBN303H8D	809 943 88	—	9.80	33.4	3.65	6.6	2.68	9.2	1.7	
			C-SBN303H8H	809 947 88	—	9.80	33.4	3.65	6.6	2.68	9.2	1.7	Тандем
	3.7	42.4	C-SBP130H38A	—	—	10.9	37.2	3.75	6.8	2.91	9.9	1.7	
			C-SBP130H38B	—	—	10.9	37.2	3.75	6.8	2.91	9.9	1.7	Тандем
	4	46.4	C-SBP140H38A	—	—	11.7	39.9	4.00	7.2	2.93	10.0	1.7	
			C-SBP140H38B	—	—	11.7	39.9	4.00	7.2	2.93	10.0	1.7	Тандем
	4.6	51.6	C-SBP160H38C	—	—	13.2	45.0	4.30	7.6	3.07	10.5	1.4	
			C-SBN353H8D	809 948 88	—	13.0	44.4	4.65	8.0	2.80	9.5	1.7	
		51.8	C-SBN353H8H	809 949 88	—	13.0	44.4	4.65	8.0	2.80	9.5	1.7	Тандем
			C-SBP160H38A	—	—	13.2	45.0	4.60	8.6	2.87	9.8	1.7	
		C-SBP160H38B	—	—	13.2	45.0	4.60	8.6	2.87	9.8	1.7	Тандем	
	5	55.7	C-SBN373H8D	809 953 88	—	14.1	48.1	4.75	8.2	2.97	10.1	1.7	
			C-SBN373H8H	809 957 88	—	14.1	48.1	4.75	8.2	2.97	10.1	1.7	Тандем
			C-SBP170H38A	—	—	14.2	48.5	4.75	8.7	2.99	10.2	1.7	
			C-SBP170H38B	—	—	14.2	48.5	4.75	8.7	2.99	10.2	1.7	Тандем
	5.5	60.4	C-SBP185H38A	—	—	15.2	51.9	5.20	9.3	2.92	10.0	1.7	
	6	66.8	C-SBN453H8D	809 963 88	—	16.4	56.0	5.75	9.8	2.85	9.7	1.7	
			C-SBN453H8H	809 967 88	—	16.4	56.0	5.75	9.8	2.85	9.7	1.7	Тандем
			C-SBP205H38A	—	—	16.8	57.3	5.60	10.1	3.00	10.2	1.7	
			C-SBP205H38B	—	—	16.8	57.3	5.60	10.1	3.00	10.2	1.7	Тандем
	6.8	76.0	C-SBP235H38A	—	—	19.9	67.9	6.55	11.3	3.04	10.4	1.4	
			C-SBP235H38B	—	—	19.9	67.9	6.55	11.3	3.04	10.4	1.4	Тандем
	7	77.4	C-SBN523H8D	809 973 88	—	19.2	65.5	6.75	11.6	2.84	9.7	1.7	
			C-SBN523H8H	809 977 88	—	19.2	65.5	6.75	11.6	2.84	9.7	1.7	
	8	89.2	C-SCP270H38A	—	—	22.4	76.4	7.40	13.1	3.03	10.3	2.8	
			C-SCP270H38B	—	—	22.4	76.4	7.40	13.1	3.03	10.3	2.8	Тандем
		90.6	5CB091SA01	—	—	23.2	79.2	7.60	13.8	3.05	10.4	2.5	
			5CB091SA04	—	—	23.2	79.2	7.60	13.8	3.05	10.4	2.5	Тандем
	10	104.1	C-SCP315H38A	—	—	26.0	88.7	8.60	14.9	3.02	10.3	2.8	
			C-SCP315H38B	—	—	26.0	88.7	8.60	14.9	3.02	10.3	2.8	Тандем
			C-SCP315H38M	—	—	27.4	93.5	8.98	14.9	3.05	10.4	2.8	
		110.2	5CB110SA01	—	—	27.4	93.5	8.98	15.7	3.05	10.4	2.5	
			5CB110SA04	—	—	27.4	93.5	8.98	15.7	3.05	10.4	2.5	Тандем
	11	120.2	C-SCP360H38A	—	—	29.8	101.7	9.90	16.9	3.01	10.3	2.8	
			C-SCP360H38B	—	—	29.8	101.7	9.90	16.9	3.01	10.3	2.8	Тандем
		120.3	C-SCP360H38M	—	—	31.5	107.5	9.80	18.1	3.21	11.0	2.8	
	12	127.8	C-SCP400H38M	—	—	32.6	111.2	10.20	18.8	3.20	10.9	2.8	
		131.9	C-SCP400H38A	—	—	32.8	111.9	10.90	18.3	3.01	10.3	2.8	
			C-SCP400H38B	—	—	32.8	111.9	10.90	18.3	3.01	10.3	2.8	Тандем
	13	148.8	C-SCP435H38B	—	—	37.6	128.3	12.10	21.4	3.11	10.6	2.8	Тандем
	15	171.2	C-SCP510H38B	—	—	43.9	149.8	13.80	24.4	3.18	10.9	3.5	Тандем
	20	227	5CF227SA01	—	—	57.8	197.2	18.50	32.6	3.12	10.7	4.5	Пример
	20	227	5CF227SA04	—	—	57.8	197.2	18.50	32.6	3.12	10.7	4.5	Пример, Тандем
	25	277	5CF277SA01	—	—	74.1	252.8	22.30	38.6	3.32	11.3	4.5	
	25	277	5CF277SA04	—	—	74.1	252.8	22.30	38.6	3.32	11.3	4.5	Пример, Тандем

■ B5 (50Hz 220-240V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
	л.с.	см3/оборот	кВт	кBTU/h	кВт	A	W/W	BTU/Wh	Liter				
1Ph	3.5	39.9	C-SBP120H15A	—	PSC	10.0	34.0	3.60	16.9	2.76	9.4	1.4	
	4	46.4	C-SBP140H15A	—	PSC	11.6	39.6	4.10	19.1	2.83	9.7	1.4	
	4.6	51.8	C-SBP160H15A	—	PSC	13.0	44.4	4.65	21.7	2.80	9.5	1.4	
	5.5	60.4	C-SBP185H15A	—	PSC	15.1	51.5	5.35	24.7	2.82	9.6	1.4	

Условия: Температура конденсации 54.4°C, Температура кипения 7.2°C, Переохлаждение 8.3K, Перегрев 11.1K