

■ B8 (50Hz 380-415V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
						кВт	кBTU/h			кВт	A		
3Ph	3.5	55.7	C-SBS120H38A	—	—	10.0	34.1	3.20	6.0	3.13	10.7	1.7	
			C-SBN263H8A	809 930 88	—	9.6	32.8	3.35	6.2	2.87	9.8	1.7	
	4	66.8	C-SBS145H38A	—	—	12.0	40.9	3.80	6.9	3.16	10.8	1.7	
			C-SBN303H8A	809 940 88	—	11.6	39.6	3.80	6.8	3.05	10.4	1.7	
			C-SBN303H8G	809 946 88	—	11.6	39.6	3.80	6.8	3.05	10.4	1.7	Тандем
	4.2	70.5	C-SBS150H38C	—	—	12.8	43.7	4.05	7.2	3.16	10.8	1.4	
	4.4	73.2	C-SBS160H38A	—	—	13.0	44.4	4.15	7.4	3.13	10.7	1.7	
	4.5	76.0	C-SBS165H38C	—	—	13.6	46.4	4.41	7.7	3.08	10.5	1.7	
	4.6	77.4	C-SBN353H8A	809 942 88	—	13.4	45.7	4.60	8.1	2.91	9.9	1.7	
			C-SBN353H8G	809 944 88	—	13.4	45.7	4.60	8.1	2.91	9.9	1.7	Тандем
			C-SBS165H38P	—	—	13.4	45.7	4.60	8.8	2.91	9.9	1.7	ТЗ
	5	83.2	C-SBN373H8A	809 950 88	—	14.5	49.5	4.95	8.5	2.93	10.0	1.7	
			C-SBN373H8G	809 956 88	—	14.5	49.5	4.95	8.5	2.93	10.0	1.7	Тандем
		83.7	C-SBS180H38C	—	—	14.7	50.2	4.77	8.2	3.08	10.5	1.7	
	5.5	90.6	C-SBS195H38A	—	—	16.2	55.3	5.22	9.3	3.10	10.6	1.7	
	6	100.0	C-SBN453H8A	809 960 88	—	17.6	60.1	5.80	9.9	3.03	10.4	1.7	
			C-SBN453H8G	809 966 88	—	17.6	60.1	5.80	9.9	3.03	10.4	1.7	Тандем
			C-SBS215H38P	—	—	17.6	60.1	5.80	10.6	3.03	10.4	1.7	ТЗ
	7	110.2	C-SBS235H38A	—	—	19.5	66.5	6.30	11.2	3.10	10.6	1.7	
			C-SBS235H38B	—	—	19.5	66.5	6.30	11.2	3.10	10.6	1.7	Тандем
	7.7	131.9	C-SCN583H8H	809 184 88	—	23.6	80.5	7.55	13.1	3.13	10.7	2.8	
			C-SCN583H8K	809 186 88	—	23.6	80.5	7.55	13.1	3.13	10.7	2.8	Тандем
	8	137.0	C-SCN603H8H	809 181 88	—	24.5	83.6	7.75	13.2	3.16	10.8	2.8	
			C-SCN603H8K	809 183 88	—	24.5	83.6	7.75	13.2	3.16	10.8	2.8	Тандем
			C-SCN603H8T	809 185 88	—	24.5	83.6	7.75	13.2	3.16	10.8	2.8	смотровое стекло
	9	148.8	C-SCN673H8H	809 191 88	—	26.5	90.4	8.50	14.4	3.12	10.6	2.8	
			C-SCN673H8K	809 193 88	—	26.5	90.4	8.50	14.4	3.12	10.6	2.8	Тандем
	10	171.2	C-SCN753H8H	809 101 88	—	29.9	102.0	9.35	15.9	3.20	10.9	2.8	
			C-SCN753H8K	809 103 88	—	29.9	102.0	9.35	15.9	3.20	10.9	2.8	Тандем
			C-SCN753H8T	809 105 88	—	29.9	102.0	9.35	15.9	3.20	10.9	2.8	смотровое стекло
	12	205.4	C-SCN903H8H	809 121 88	—	34.9	119.1	11.30	18.9	3.09	10.5	2.8	
			C-SCN903H8K	809 123 88	—	34.9	119.1	11.30	18.9	3.09	10.5	2.8	Тандем
			C-SCN903H8T	809 125 88	—	34.9	119.1	11.30	18.9	3.09	10.5	2.8	смотровое стекло

■ B5 (50Hz 220-240V)

Количество фаз	Номинальная мощность	Объем сжатия	Модель компрессора	Код компрессора	Пусковой блок	50Hz						Заправка маслом	Примечание
						Производительность		Мощность двигателя	Ток	COP			
	л.с.	см3/оборот	кВт	кBTU/h	кВт	A	W/W	BTU/Wh	Liter				
1Ph	3.5	55.7	C-SBS120H15A	—	PSC	9.70	33.1	3.40	16.1	2.85	9.7	1.7	
	4	66.8	C-SBS145H15A	—	PSC	11.8	40.3	4.00	19.4	2.95	10.1	1.7	
	4.6	77.4	C-SBS165H15A	—	PSC	13.7	46.7	4.80	22.6	2.85	9.7	1.4	
	5	83.2	C-SBS180H15A	—	PSC	14.7	50.2	5.05	24.1	2.91	9.9	1.4	
	5.8	93.1	C-SBS200H15H	—	PSC	16.4	56.0	5.55	25.7	2.95	10.1	1.7	смотровое стекло
3Ph	3.5	55.7	C-SBN263H5A	809 930 85	—	9.85	33.6	3.35	10.6	2.94	10.0	1.7	
	4	66.8	C-SBN303H5A	809 940 85	—	11.5	39.2	3.85	12.9	2.99	10.2	1.7	
	5	83.2	C-SBN373H5A	809 950 85	—	14.7	50.2	5.05	15.1	2.91	9.9	1.7	
	6	100.0	C-SBN453H5A	809 960 85	—	17.7	60.4	5.90	18.0	3.00	10.2	1.7	
	7.7	131.9	C-SCN583H5H	809 184 85	—	23.7	80.9	7.55	23.1	3.14	10.7	2.8	
	8	137.0	C-SCN603H5H	809 181 85	—	24.2	82.6	7.70	23.3	3.14	10.7	2.8	
	10	171.2	C-SCN753H5H	809 101 85	—	29.9	102.0	9.40	28.1	3.18	10.9	2.8	
	12	205.4	C-SCN903H5H	809 121 85	—	34.8	118.7	11.30	33.3	3.08	10.5	2.8	

Условия: Температура конденсации 54.4°C, Температура кипения 7.2°C, Переохлаждение 8.3K, Перегрев 9K