

Тип мотора	Электрические параметры	Охлаждение компрессора (в соответствии со спецификацией)	Вес [кг]	Размеры					Альтернативное расположение возможно
				Высота [мм]		Расположение патрубков/I.D. [мм]			
				A	B	Всасы- вание	Сервисный	Нагне- тание	
RSIR/RSCR	198-254 V, 50 Hz	S	8	175	169	6.2	4.5	5.0	X
RSIR/RSCR	198-254 V, 50 Hz	S	8	175	169	6.2	4.5	5.0	X
RSIR/RSCR	198-254 V, 50 Hz	S	8	175	169	6.2	4.5	5.0	
RSIR/RSCR	198-254 V, 50 Hz	S	8	175	169	6.2	4.5	5.0	X
RSIR/RSCR	198-254 V, 50 Hz	S	8	175	169	6.2	6.0	5.0	
RSCR	198-254 V, 50 Hz	S	8,4	175	169	6.2	4.5	5.0	
RSCR	198-254 V, 50 Hz	S	8,4	175	169	6.2	4.5	5.0	
RSCR	198-254 V, 50 Hz	S	8,4	175	169	6.2	4.5	5.0	
RSCR	198-254 V, 50 Hz	S	8,4	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,2	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,2	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,2	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,3	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,3	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,3	175	169	6.2	6.0	5.0	X
RSCR	198-254 V, 50 Hz	S	9,3	175	169	6.2	6.0	5.0	
RSCR	198-254 V, 50 Hz	S	9,4	175	169	6.2	6.0	5.0	X

Тип мотора	Электрические параметры	Охлаждение компрессора (в соответствии со спецификацией)	Вес [кг]	Размеры					
				Высота [мм]		Расположение патрубков/I.D. [мм]			Альтернативное расположение возможно
				A	B	Всасы- вание	Сервисный	Нагне- тание	
RSIR	187-264 V, 50 Hz	S	7,6	159	165.5	6.15	6.00	5.15	X
RSIR	187-264 V, 50 Hz	S	7,9	159	165.5	6.15	6.00	5.15	X
RSIR	187-264 V, 50 Hz	S	8,6	167	173.5	6.15	6.00	5.15	X
RSIR/RSCR	187-264 V, 50 Hz	S	7,8	159	165.5	6.15	6.00	5.15	X
RSIR/RSCR	187-264 V, 50 Hz	S	7,9	159	165.5	6.15	6.00	5.15	X
RSIR/RSCR	187-264 V, 50 Hz	S	7,9	159	165.5	6.15	6.00	5.15	X
RSIR/RSCR	187-264 V, 50 Hz	S	8,3	167	173.5	6.15	6.00	5.15	X
RSIR/RSCR	187-264 V, 50 Hz	S	8,5	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	7,9	159	165.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	7,9	159	165.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,2	159	165.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,5	159	165.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,2	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,6	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,6	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	8,8	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9,2	167	173.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9,6	170	176.5	6.15	6.00	5.15	X
RSCR	187-264 V, 50 Hz	S	9,6	170	176.5	6.15	6.00	5.15	X
RSIR/RSCR	170-264 V, 50 Hz	S	8,2	167	173.5	6.15	6.00	5.15	X
RSIR/RSCR	170-264 V, 50 Hz	S	8,1	167	173.5	6.15	6.00	5.15	X
RSIR/RSCR	170-264 V, 50 Hz	S	8,6	167	173.5	6.15	6.00	5.15	X
RSIR/RSCR	170-264 V, 50 Hz	S	8,9	167	173.5	6.15	6.00	5.15	X

Technical drawing of the 8241 pressure washer, showing front, side, and top views with dimensions in mm.

Front View Dimensions:

- Overall width: 204
- Inner width: 170
- Motor housing width: 100
- Motor housing height: 70
- Motor housing depth: 35
- Motor housing diameter: $\varnothing 9$
- Motor housing diameter: $\varnothing 16$

Side View Dimensions:

- Overall width: 206
- Motor housing width: 100
- Motor housing height: 70
- Motor housing depth: 35
- Motor housing diameter: $\varnothing 9$
- Motor housing diameter: $\varnothing 16$

Top View Dimensions:

- Overall width: 8241
- Overall height: 130
- Motor housing width: 50
- Motor housing height: 60.5
- Motor housing depth: 46
- Motor housing diameter: $\varnothing 9$
- Motor housing diameter: $\varnothing 16$

Technical drawing of the DLE / DLY / DLX container, showing three views: top, side, and front.

Top View:

- Overall width: 200
- Inner width: 170
- Overall height: 178
- Height from base to top edge: 100
- Height from base to handle: 70
- Handle diameter: $\varnothing 9$
- Top edge diameter: $\varnothing 16$

Side View:

- Overall width: 184.2
- Height from base to top edge: 134.5
- Overall height: 233
- Height from base to handle: 73.6
- Height from base to top edge: 97
- Angle of handle: 67°
- Angle of top edge: 25°
- Angle of handle: 18°

Front View:

- Overall width: 157
- Height from base to top edge: 74.4
- Height from base to handle: 59.5
- Overall height: 114.4
- Height from base to handle: 98.5
- Height from base to top edge: 98
- Height from base to top edge: 60.7
- Height from base to top edge: 73
- Angle of handle: 58°
- Angle of top edge: 41°
- Angle of handle: 35°

Reference number: 8735

Technical drawing of the NLX / NLU (NLE similar) helmet, showing three views: top, side, and front.

Top View Dimensions:

- Top width: 204
- Main body width: 170
- Bottom width: 178
- Left side height: 100
- Left side shell height: 70
- Right side shell diameter: $\varnothing 16$

Side View Dimensions:

- Top width: 205
- Height: A, B
- Height from base to top of side shell: 93.5
- Angle of side shell: 25°
- Height from base to top of side shell (inner): 102.5
- Height from base to top of side shell (outer): 71
- Width: 254
- Angle of side shell (inner): 21°
- Angle of side shell (outer): 15°

Front View Dimensions:

- Height: 166
- Height from base to top of side shell: 72
- Height from base to top of side shell (inner): 60.5
- Angle of side shell: 51°
- Angle of side shell (inner): 55°
- Angle of side shell (outer): 24°
- Width: 113
- Width: 91
- Width: 133
- Height from base to top of side shell (outer): 57
- Height from base to top of side shell (inner): 81

Reference number: 8649

Technical drawing of the KAPPA 8778 outdoor heater, showing three views: top, side, and front.

Top View Dimensions:

- Overall width: 231
- Inner width: 204
- Inner width: 170
- Height: 100
- Height: 70
- 6x Ø16 (6 holes of diameter 16)

Side View Dimensions:

- Overall height: 136
- Height: 105
- Height: 71
- Height: 10
- Height: 18
- Angle: 32°
- Angle: 35°
- Angle: 14°
- Angle: 53°

Front View Dimensions:

- Overall height: 151
- Overall width: 239
- Height: 10
- Height: 18
- Angle: 32°

Model number: 8778

Technical drawing of the DELTA 8779 portable toilet, showing three views: top, side, and front.

Top View:

- Overall diameter: $\varnothing 78.5$
- Height: 84
- Flange diameter: 58
- Flange thickness: 32
- Flange angle: 33°
- Base diameter: 70
- Base thickness: 65
- Base angle: 73°

Side View:

- Overall height: 130
- Height to top of tank: 96
- Height to bottom of tank: 83
- Height to top of side panel: 91
- Height to bottom of side panel: 93
- Side panel angle: 73°
- Side panel thickness: 20

Front View:

- Overall height: 147
- Overall width: 160
- Width to center of tank: 142
- Width to center of side panel: 159
- Width to center of front panel: 20
- Front panel angle: 50°
- Front panel thickness: 20
- Front panel angle: 73°

Model number: 8779

Размеры конденсатного поддона

Габаритные размеры в сборе с конденсатным поддоном

**Габаритные размеры
в сборе с крепежной площадкой**

**Габаритные размеры
в сборе с конденсатным поддоном**