



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0820-1UR01	B, H	12	10.2 ~ 13.8	41.87	0.223	4000	0.27	3.24	0.30	39.6	57
KF0820-1SR01	B, H, S			36.55	0.178	3500	0.20	2.40	0.22	35.5	
KF0820-1H-01	B, H, S			31.09	0.135	3000	0.14	1.68	0.15	31.4	
KF0820-1M-01	B, H, S			25.75	0.097	2500	0.08	0.96	0.09	26.5	
KF0820-1L-01	B, H, S			20.44	0.065	2000	0.06	0.72	0.07	21.3	
KF0820-1E-01	B, H, S			15.20	0.039	1500	0.04	0.48	0.05	14.2	
KF0820-2UR01	B, H	24	20.4 ~ 27.6	41.87	0.223	4000	0.13	1.56	0.15	39.6	
KF0820-2SR01	B, H, S			36.55	0.178	3500	0.10	2.40	0.11	35.5	
KF0820-2H-01	B, H, S			31.09	0.135	3000	0.07	1.68	0.08	31.4	
KF0820-2M-01	B, H, S			25.75	0.097	2500	0.06	1.44	0.07	26.5	
KF0820-2L-01	B, H, S			20.44	0.065	2000	0.04	0.96	0.05	21.3	
KF0820-2E-01	B, H, S			15.20	0.039	1500	0.03	0.72	0.04	14.2	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

