



◎构造及原理 [Structure and principle] :

(275克高镀锌风机)

The MW High Class Fan is composed of a blade, motor, outer frame protecting nets and supporting frames and shutters.The shutters are opened by the Push-pull Centrifugal system. The major parts are made of galvanized steel sheets(180g/275g/m2 zinc coating)and stainless steel sheets. Based on sound aerodynamic principles, wind resistance is minimized and efficient airflow is achieved. All products are used in a wide range of settings, including various types of farms, greenhouses and factory buildings.

◎主要配件 [The main parts] :



◎技术参数 [Technical parameters] :

型号规格 Model specifications	风叶直径 Diameter blades (mm)	风叶转速 (转/分) Blades rotational speed rpm	电机转速 (转/分) Motor rotational speed rpm	风 量 Air flow (m³/h)	全 压 (Pa) Total pressure	噪音 (分贝) Noise decibels	输入功率 (W) Import power	额定电压 (V) Rated voltage	高 (mm) Height	宽 (mm) Width	厚 (mm) Thickness
MW-800 型	710 (28")	650	1400	18000	60	≤70	370	380	800	800	450
MW-1000型	910 (36")	650	1400	26000	60	≤70	550	380	1000	1000	450
MW-1100型	1000(40")	600	1400	33000	70	≤70	750	380	1100	1100	450
MW-1380型	1270(50")	440	1400	43500	56	≤70	1100	380	1380	1380	450
MW-1530型	1400(55")	420	1400	51000	56	≤75	1500	380	1530	1530	450

由于产品不断改进, 各种参数如有变动, 恕不另行通知。



Fans mainly consists of blade, motor, frame, protect net, bracing cage, shutters. The motor drives blade to cause air flow and louver window can open and close automatically to keep the dust from entering.

■主要技术参数: Technical parameters

型号规格 Model specifications	风叶直径 Diameter blades (mm)	风叶转速 (转/分) Blades rotational speed rpm	电机转速 (转/分) Motor rotational speed rpm	风 量 Air flow (m³/h)	全 压 (Pa) Total pressure	噪音 (分贝) Noise decibels	输入功率 (W) Import power	额定电压 (V) Rated voltage	高 (mm) Height	宽 (mm) Width	厚 (mm) Thickness
MWF-600(24 ")	500	680	1400	6500	60	≤60	370	380	600	600	370
MWF-800(29 ")	710	660	1400	22000	60	≤60	370	380	800	800	400
MWF-900(30 ")	750	630	1400	28000	65	≤65	550	380	900	900	400
MWF-1000(36 ")	900	610	1400	30000	70	≤70	550	380	1000	1000	400
MWF-1100(40 ")	1000	600	1400	32500	70	≤70	750	380	1100	1100	400
MWF-1220(44 ")	1100	460	1400	38000	73	≤70	1100	380	1220	1220	400
MWF-1380(50 ")	1250	439	1400	44000	56	≤70	1100	380	1380	1380	400
MWF-1530(56 ")	1400	325	1400	55800	60	≤70	1500	380	1530	1530	400

由于产品不断更新, 技术参数如有改动恕不另行通知。

