

## Inflatable Blower European Standard (CE Certification)

### Product Characteristic

- Double-sided fan blade design, larger air volume and wind pressure, strong heat dissipation, ensuring long-term continuous and stable work.
- Energy-efficient motor, energy-saving, high efficiency, durable, strong core brings continuous and stable wind pressure operation.
- Advanced design concept, low noise and energy saving.
- Integrated fuselage, closed design, safe and reliable.
- Wide application range, designed for different scenes.
- Rain-proof, flame-retardant and cold-resistant shell, after thousands of high voltage test, can handle various unexpected situations with peace of mind, and can be used safely in any weather.
- Product usage:bouncy castles / jumping bed / tent / and other uses.



### Product Drawing



### Technical Parameters

| Model       | Voltage (V) | Frequency (Hz) | Power (W) | Boosting pressure(Pa) | Air flow (m³/h) | Product size (cm) | Caliber (mm) | N.W./G.W. (Kg) | Package size (cm) |
|-------------|-------------|----------------|-----------|-----------------------|-----------------|-------------------|--------------|----------------|-------------------|
| LWA-370-01  | 230         | 50             | 370       | 1500                  | 750             | 37×18×37          | 110          | 4.1 / 5.1      | 38×21×38.5        |
| LWA-550-01  | 230         | 50             | 550       | 1800                  | 800             | 37×18×37          | 110          | 4.5 / 5.5      | 38×21×38.5        |
| LWA-680-01  | 230         | 50             | 680       | 1950                  | 850             | 43×22×43          | 120          | 6 / 7.6        | 44×23.5×45        |
| LWA-750-01  | 230         | 50             | 750       | 2200                  | 900             | 43×24×43          | 140          | 7 / 8.6        | 44×25.5×45        |
| LWA-950-01  | 230         | 50             | 950       | 2400                  | 1050            | 43×24×43          | 140          | 7.2 / 8.8      | 44×25.5×45        |
| LWA-1100-01 | 230         | 50             | 1100      | 2550                  | 1200            | 43×24×43          | 140          | 7.5 / 9.1      | 44×25.5×45        |

## Inflatable Blower US Standard (UL/ETL Certification)

### Product Characteristic

- Double-sided fan blade design, larger air volume and wind pressure, strong heat dissipation, ensuring long-term continuous and stable work.
- Energy-efficient motor, energy-saving, high efficiency, durable, strong core brings continuous and stable wind pressure operation.
- Advanced design concept, low noise and energy saving.
- Integrated fuselage, closed design, safe and reliable.
- Wide application range, designed for different scenes.
- Rain-proof, flame-retardant and cold-resistant shell, after thousands of high voltage test, can handle various unexpected situations with peace of mind, and can be used safely in any weather.
- Product usage:bouncy castles / jumping bed / tent / and other uses.



### Product Drawing



### Technical Parameters

| Model       | Voltage (V) | Frequency (Hz) | Power (W) | Boosting pressure(Pa) | Air flow (m³/h) | Product size (cm) | Caliber (mm) | N.W./G.W. (Kg) | Package size (cm) |
|-------------|-------------|----------------|-----------|-----------------------|-----------------|-------------------|--------------|----------------|-------------------|
| LWA-370-02  | 120         | 60             | 370       | 1650                  | 760             | 37×18×37          | 110          | 4.1 / 5.1      | 38×21×38.5        |
| LWA-480-01  | 120         | 60             | 480       | 1800                  | 800             | 37×18×37          | 110          | 4.3 / 4.3      | 38×21×38.5        |
| LWA-550-02  | 120         | 60             | 550       | 1900                  | 850             | 37×18×37          | 110          | 4.5 / 5.5      | 38×21×38.5        |
| LWA-680-02  | 120         | 60             | 680       | 2200                  | 900             | 43×22×43          | 120          | 6 / 7.2        | 44×23.5×45        |
| LWA-750-02  | 120         | 60             | 750       | 2550                  | 960             | 43×24×43          | 120          | 6.2 / 7.8      | 44×25.5×45        |
| LWA-950-02  | 120         | 60             | 950       | 2600                  | 1050            | 43×24×43          | 140          | 7.1 / 8.7      | 44×25.5×45        |
| LWA-1100-02 | 120         | 60             | 1100      | 2650                  | 1200            | 43×24×43          | 140          | 7.5 / 9.1      | 44×25.5×45        |