


LWAE-630 Serise




Product Characteristic

- Material : PA66
- Insulation Class: F
- Operation Temperature: -25 °C ~ +60 °C
- Protection: Tach output, Locked-Rotor protection, Reverse Polarity, Over-voltage Protection, Soft Start Protection
- Type of Protection: IP54
- Motor Type: BLEC Motor
- Technical Features: Control input 0-10VDC/PWM/RS485




Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Current (A)	Power [W(@0Pa)]	Speed (RPM)	Air Volume (m³/h)	Noise [dB(A)]
LWAE3G630TS-5PEW-11	400	50/60	1.57	887	1200	13670	74



LWAE-710 Serise



Product Characteristic

- Material : Aluminium alloy
- Insulation Class: F
- Operation Temperature: -25 °C ~ +60 °C
- Protection: Tach output, Locked-Rotor protection, Reverse Polarity, Over-voltage Protection, Soft Start Protection
- Type of Protection: IP54
- Motor Type: BLEC Motor
- Technical Features: Control input 0-10VDC/PWM



Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Current (A)	Power [W(@0Pa)]	Speed (RPM)	Air Volume (m³/h)	Noise [dB(A)]
LWAE3G710TS-5MKW-01	230	50/60	3.5	520	960	13905	75

