


LWBE-175 Serise




Product Characteristic

- Impeller Material: PA6+GF
- Direction of Rotation: Clockwise, seen on rotor
- Protection Class: IP55
- Mounting Position: Horizontal or Vertical
- Bearing: Maintenance-free ball bearings
- Protection: Tach output, Locked-Rotor protection Reverse Polarity, Over-voltage protection, Soft Start
- Supply Voltage: 230V, 50/60Hz
- Mode of Operation: S1
- Insulation Class: F
- Operation Temperature: -25 °C ~ +60 °C
- Technical Features: Control input 0-10VDC/PWM




Technical Specifications

Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G175-072NS-07	230	170	1.2	912	876	4760	71
LWBE3G175-072NU-19	115	170	2.4	912	876	4760	71



zakaz@ventilatorry.ru +7 (495) 133-95-09

LWBE-190 Serise




Product Characteristic

- Impeller Material: PA6+GF
- Direction of Rotation: Clockwise, seen on rotor
- Protection Class: IP55
- Mounting Position: Horizontal or Vertical
- Bearing: Maintenance-free ball bearings
- Protection: Tach output, Locked-Rotor protection Reverse Polarity, Over-voltage protection, Soft Start
- Supply Voltage: 230V, 50/60Hz
- Mode of Operation: S1
- Insulation Class: F
- Operation Temperature: -25 °C ~ +60 °C
- Technical Features: Control input 0-10VDC/PWM



Technical Specifications

Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G190-072NS-14	230	64	0.53	639	453	2940	65
LWBE3G190-072NU-18	115	64	1.1	639	453	2940	65



zakaz@ventilatorry.ru +7 (495) 133-95-09