


● Impeller Material:	PA6+GF
● Supply Voltage:	230V,50/60Hz
● Mode of Operation:	S1
● Protection Class:	IP55
● Insulation Class:	F
● Operation Temperature:	-25℃ ~ +60℃
● Technical Feature:	Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection.



Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G190-072PS-02	230	115	0.9	855	876	3800	71



Technical drawing of the 1000W 230V 50Hz electric heater, showing side, front, and top views with dimensions.

Side View Dimensions:

- Overall height: 190
- Mounting bracket height: 72
- Heater body height: 133
- Mounting bracket width: 27
- Mounting bracket thickness: 1.8
- Heater body width: 38
- Heater body depth: 68.5 ± 1
- Heater body length: 80.4
- Heater body material: L=500mm

Front View Dimensions:

- Overall width: 170
- Heater body width: 158
- Mounting bracket width: 125.5
- Mounting bracket thickness: 4
- Mounting bracket material: 4-Ø1.5
- Mounting bracket length: 14
- Mounting bracket depth: 0.9

Top View Dimensions:

- Overall diameter: Ø190
- Heater body diameter: Ø133
- Mounting bracket diameter: Ø72
- Mounting bracket material: 4-Ø1.5
- Heater body material: L=500mm

Technical drawing of the L=500mm LED light fixture, showing three views: top, side, and bottom.

Top View: A square frame with a side length of 226 mm. The central circular lens has a diameter of $\varnothing 265$ mm. There are four mounting holes, each with a diameter of 4 mm.

Side View: Shows the internal components and the depth of the fixture. The dimensions are 77.6 mm, 81.6 mm, and 89 mm.

Bottom View: A square frame with a side length of 202 mm. The central circular cutout has a diameter of $\varnothing 265$ mm. There are four mounting holes, each with a diameter of 4 mm. The label L=500mm is shown.