


LWBE-450 Serise




Product Characteristic

- | | | | |
|--------------------------|---|--------------------------|---------------------------|
| • Impeller Material: | Aluminum Alloy | • Supply Voltage: | 400V,50/60Hz |
| • Direction of Rotation: | Clockwise,seen on rotor | • Mode of Operation: | S1 |
| • Protection Class: | IP54 | • Insulation Class: | F |
| • Mounting Position: | Horizontal or Vertical | • Operation Temperature: | -25 C ~+60 C |
| • Bearing: | Maintenance-free ball bearings | • Technical Features: | Control input 0-10VDC/PWM |
| • Protection: | Tach output,Locked-Rotor protection Reverse Polarity,Over-voltage protection,Soft Start | | |




Technical Specifications

Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-138NT-12	400	900	/	7182	730	1610	/



zakaz@ventilatorry.ru +7 (495) 133-95-09

LWBE-450 Serise




Product Characteristic

- | | | | |
|--------------------------|---|--------------------------|---------------------------|
| • Impeller Material: | Aluminum Alloy | • Supply Voltage: | 400V,50/60Hz |
| • Direction of Rotation: | Clockwise,seen on rotor | • Mode of Operation: | S1 |
| • Protection Class: | IP54 | • Insulation Class: | F |
| • Mounting Position: | Horizontal or Vertical | • Operation Temperature: | -25 C ~+60 C |
| • Bearing: | Maintenance-free ball bearings | • Technical Features: | Control input 0-10VDC/PWM |
| • Protection: | Tach output,Locked-Rotor protection Reverse Polarity,Over-voltage protection,Soft Start | | |



Technical Specifications

Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-138NT-08	400	910	3.4	7828	824	1720	/



zakaz@ventilatorry.ru +7 (495) 133-95-09