


LWCD-40 Series

Product Characteristic

- Motor Type : 3 Phase BLDC Motor
- Housing Material : Steel+Aluminum Alloy
- Blade Material : Aluminum Alloy
- Insulation Class : B
- Bearing Type: Ball bearing
- Operation Temperature : - 25 ℃ ~ +60 ℃




Technical Specifications

Model	A (mm)	B (mm)	C (mm)	Voltage (V)	Current (A)	Speed (RPM)	Pressure (Pa)	Air Flow (m³/h)	Noise [dB(A)]	Blower
LWCD-4090LN-06	149	108	98	12	0.12	2400	20	34	33	Single
LWCD-4090MN-07	149	108	98	24	0.06	2400	20	34	33	Single
LWCD-40150LN-06	210	170	160	12	0.14	2400	21	55	33	Single
LWCD-40150MN-07	210	170	160	24	0.08	2400	21	55	33	Single
LWCD-40190LN-06	249	208	198	12	0.16	2400	22	69	34	Single
LWCD-40190MN-07	249	208	198	24	0.09	2400	22	69	34	Single
LWCD-40250LN-06	300	260	250	12	0.18	2400	23	87	35	Single
LWCD-40250MN-07	300	260	250	24	0.11	2400	23	87	35	Single
LWCD-40290LN-06	352	310	300	12	0.2	2400	24	104	35	Single
LWCD-40290MN-07	352	310	300	24	0.13	2400	24	104	35	Single
LWCD-40350LN-06	417	358	348	12	0.24	2400	24	121	36	Single
LWCD-40350MN-07	417	358	348	24	0.15	2400	24	121	36	Single
LWCD-40420LN-06	472	430	420	12	0.29	2400	25	146	37	Single
LWCD-40420MN-07	472	430	420	24	0.17	2400	25	146	37	Single

LWCD-40 Series

Product Characteristic

- Motor Type : 3 Phase BLDC Motor
- Housing Material : Steel+Aluminum Alloy
- Blade Material : Aluminum Alloy
- Insulation Class : B
- Bearing Type: Ball bearing
- Operation Temperature : - 25 ℃ ~ +60 ℃



Technical Specifications

Model	A (mm)	B (mm)	C (mm)	Voltage (V)	Current (A)	Speed (RPM)	Pressure (Pa)	Air Flow (m³/h)	Noise [dB(A)]	Blower
LWCD-40530MN-06	580	540	530	24	0.19	2400	25	176	37	Double
LWCD-40610MN-06	670	620	610	24	0.21	2400	26	203	37	Double
LWCD-40700MN-06	750	710	700	24	0.23	2400	26	232	38	Double
LWCD-40800MN-06	850	810	800	24	0.25	2000	25	236	35	Triple
LWCD-40854MN-06	904	864	854	24	0.28	2000	26	252	35	Triple
LWCD-40920MN-06	973	930	920	24	0.31	2000	26	272	36	Triple
LWCD-401055MN-06	1108	1065	1055	24	0.35	2000	27	311	36	Triple