



LWFD4010 Series

Product Characteristic

Material:	Frame: Plastic(UL94-VO) Impeller: Plastic(UL94-VO)
Voltage:	5VDC(4.0~5.5VDC), 12VDC(6~13.8VDC), 24VDC(12~27.6VDC)
Temperature:	Operation Temperature: -10~70°C(Non-condensing)
Specials:	AS, RD, FG, PWM, Temperature Control, IP56



Technical Specifications

Model	Voltage	Current	Speed	Air Volume		Static Pressure			Noise	Weight	Curve
	V	A	RPM	CFM	m³/min	mm-H2O	Inch-H2O	Pa	dBA	g	
LWFD4010KX-01	5	0.4	9000	2.7	0.08	7.5	0.29	73	33.9	13g	①
LWFD4010KH-02	5	0.35	8000	2.4	0.07	5.9	0.23	58	31.3	13g	②
LWFD4010KM-03	5	0.3	7000	2.1	0.06	4.5	0.18	44	28.4	13g	③
LWFD4010KL-04	5	0.25	6000	1.8	0.05	3.3	0.13	33	25.1	13g	④
LWFD4010KD-05	5	0.2	5000	1.5	0.04	2.3	0.09	23	21.1	13g	⑤
LWFD4010LX-01	12	0.16	9000	2.7	0.08	7.5	0.29	73	35.2	13g	①
LWFD4010LH-02	12	0.14	8000	2.4	0.07	5.9	0.23	58	32.6	13g	②
LWFD4010LM-03	12	0.12	7000	2.1	0.06	4.5	0.18	44	29.7	13g	③
LWFD4010LL-04	12	0.1	6000	1.8	0.05	3.3	0.13	33	26.4	13g	④
LWFD4010LD-05	12	0.08	5000	1.5	0.04	2.3	0.09	23	22.4	13g	⑤
LWFD4010MX-01	24	0.1	9000	2.7	0.08	7.5	0.29	73	35.2	13g	①
LWFD4010MH-02	24	0.08	8000	2.4	0.07	5.9	0.23	58	32.6	13g	②
LWFD4010MM-03	24	0.06	7000	2.1	0.06	4.5	0.18	44	29.7	13g	③
LWFD4010ML-04	24	0.05	6000	1.8	0.05	3.3	0.13	33	26.4	13g	④
LWFD4010MD-05	24	0.04	5000	1.5	0.04	2.3	0.09	23	22.4	13g	⑤

