



Вентиляторы LITENED

VRS — шумоизолированные



Типоразмер	Обозначение	Макс. расход воздуха, м³/ч	Макс. полное давление, Па	Мощность двигателя, кВт	Частота вращения, об/мин	Рабочий ток, А	Питание вентилятора / частотного регулятора*	А, мм	Б, мм	В, мм	Г, мм	Д, мм	Масса, кг					
50-25	VRS.22.4E	1640	316,8	0,51	1418	1,1	1~220В	710	470	635	395	615	46					
	VRS.22.4D	1930	314,5	0,516	1428	2,3/3,98	3~380В/1~220В						45,5					
	VRS.22.6D	1380	139,3	0,3	952	0,8/1,38							44,5					
	VRS.25.4E (M)	2302	375,7	1,0	1390	4,6	1~220В					650	50,5					
	VRS.25.4D (M)	2570	391,1	0,938	1461	2,2/3,8	3~380В/1~220В						50					
	VRS.25.6D (M)	1811	179,2	0,355	930	0,92/1,6							47					
50-30	VRS.25.4E	2302	375,7	1,0	1390	4,6	1~220В	710	520	635	445	650	52					
	VRS.25.4D	2570	391,1	0,938	1461	2,2/3,8	3~380В/1~220В						51,5					
	VRS.25.6D	1811	179,2	0,355	930	0,92/1,6							48,5					
	VRS.28.4E (M)	2489	488,8	1,25	1370	5,6	1~220В					730	61					
	VRS.28.4D (M)	3562	494,7	1,7	1415	3,2/5,54	3~380В/1~220В						60					
	VRS.28.6D (M)	2576	224,9	0,58	955	1,58/2,74							52					
60-30	VRS.28.4E	2489	488,8	1,25	1370	5,6	1~220В	810	520	735	445	730	63,5					
	VRS.28.4D	3562	494,7	1,7	1415	3,2/5,54	3~380В/1~220В						63					
	VRS.28.6D	2576	224,9	0,58	955	1,58/2,74							55,2					
	VRS.31.4D (M)	4510	631,6	2,2	1415	4,0/6,93	3~380В/1~220В					840	74					
	VRS.31.6D(M)	3680	270,9	0,8	930	1,5/2,6							68					
	VRS.31.4D	4510	631,6	2,2	1415	4,0/6,93							3~380В/1~220В	840	75			
60-35	VRS.31.6D	3680	270,9	0,8	930	1,5/2,6	810	570	735	495	865	69						
	VRS.35.4D (M)	5787	776,7	3,5	1422	5,9/10,2						3~380В/1~220В			91,5			
	VRS.35.6D (M)	4040	380,1	0,95	925	1,9/3,29							77					
	VRS.35.4D	5787	776,7	3,5	1422	5,9/10,2					3~380В/1~220В	910	620	835	545	865	97	
	VRS.35.6D	4040	380,1	0,95	925	1,9/3,29											83	
	VRS.35.8D	3672	213,4	0,65	670	1,4/2,3												
80-50	VRS.40.4D	6822	1020	4,7	1415	7,6	3~380В	1010	720	935	645	975	122					
	VRS.40.6D	7360	501,2	2,8	945	5,0/8,66	3~380В/1~220В						115					
	VRS.40.8D	4700	306,2	1,7	701	3,7/6,4							101					
	VRS.45.4D (M)	6558	1544,3	4,92	1265	8,3	3~380В					1100	132					
	VRS.45.6D (M)	9213	671,2	3,7	930	6,5/11,26	3~380В/1~220В						1125	740	1050	645	1100	142
	VRS.45.4D	6558	1544,3	4,92	1265	8,3												3~380В
90-50	VRS.45.6D	9213	671,2	3,7	930	6,5/11,26	3~380В/1~220В	1125	740	1050	645	1100	142					
	VRS.45.8D	7815	383,2	2,0	690	4,1/7,1							136					

