

AFQ 4 poli monofase 230 V 50 Hz
AFQ 4 Poles 1 phase 230 V 50 Hz

Ventilatore Fan type	Codice Code	Motore Motor type (*)	Portata (m3/h) Flow rate (m3/h) 1/2 (**)	Pot. ass.(W) W abs. 1/2 (**)	db (A) Lps at 3 m 1/2 (**)	Corrente Amp 1/2 (**)	T min/max °C
AFQ 315-35°/4M-A	6.800.00	110/35	1250 / 2000	136 / 123	47.3 / 50.4	0.67 / 0.63	-30/ +70
AFQ 355-30°/4M-A	6.800.01	110/35	1700 / 2700	162 / 138	49.4 / 49.3	0.76 / 0.67	-30/ +70
AFQ 400-30°/4M-B	6.800.02	110/50	2300 / 3800	250 / 200	53.6 / 52.2	1.06 / 0.85	-30/ +70
AFQ 450-30°/4M-B	6.800.03	135/50	3600 / 5900	450 / 370	59 / 57.9	1.96 / 1.57	-30/ +70
AFQ 500-30°/4M-B	6.800.04	135/70	4500 / 8200	720 / 540	62.7 / 61.4	3.29 / 2.44	-30/ +50
AFQ 560-25°/4M-B	6.800.05	135/90	6500 / 10100	900 / 630	61.2 / 59.0	3.67 / 2.77	-30/ +50

AFQ 6 poli monofase 230 V 50 Hz
AFQ 6 Poles 1 phase 230 V 50 Hz

Ventilatore Fan type	Codice Code	Motore Motor type (*)	Portata (m3/h) Flow rate (m3/h) 1/2 (**)	Pot. ass.(W) W abs. 1/2 (**)	db (A) Lps at 3 m 1/2 (**)	Corrente Amp 1/2 (**)	T min/max °C
AFQ 315-35°/6M-A	6.800.10	110/35	800 / 1350	90 / 87	40.5 / 41.7	0.43 / 0.42	-30/ +70
AFQ 355-30°/6M-A	6.800.11	110/35	1100 / 1800	93 / 89	39.6 / 40.0	0.44 / 0.43	-30/ +70
AFQ 400-30°/6M-B	6.800.12	110/50	1750 / 2650	119 / 108	44.0 / 44.6	0.54 / 0.51	-30/ +70
AFQ 450-30°/6M-B	6.800.13	135/50	2500 / 4000	174 / 105	47.2 / 49.0	0.74 / 0.64	-30/ +70
AFQ 500-30°/6M-B	6.800.14	135/50	3500 / 5500	290 / 243	51.0 / 52.7	1.40 / 1.32	-30/ +50
AFQ 560-30°/6M-B	6.800.15	135/70	4500 / 7500	400 / 330	56.1 / 55.6	1.83 / 1.6	-30/ +70
AFQ 630-30°/6M-B	6.800.16	135/90	5400 / 10200	540 / 500	58.4 / 54.2	2.4 / 2.1	-30/ +70

AFQ 8 poli monofase 230 V 50 Hz
AFQ 8 Poles 1 phase 230 V 50 Hz

Ventilatore Fan type	Codice Code	Motore Motor type (*)	Portata (m3/h) Flow rate (m3/h) 1/2 (**)	Pot. ass.(W) W abs. 1/2 (**)	db (A) Lps at 3 m 1/2 (**)	Corrente Amp 1/2 (**)	T min/max °C
AFQ 450-30°/8M-B	6.800.23	135/50	2000 / 3100	120 / 110	38.4 / 43.1	0.68 / 0.65	-30/ +70
AFQ 500-30°/8M-B	6.800.24	135/50	2400 / 4100	150 / 143	41.8 / 44.1	0.75 / 0.71	-30/ +70
AFQ 560-30°/8M-B	6.800.25	135/70	3200 / 5600	240 / 220	48.5 / 50.6	1.34 / 1.28	-30/ +60
AFQ 630-30°/8M-B	6.800.26	135/70	3600 / 7350	276 / 250	49.0 / 47.9	1.47 / 1.37	-30/ +60

(*) vedi tabelle dimensioni / see dimensional sheet / voir table des dimensions / siehe Maßblatt

(**) per i punti 1 e 2 vedi curve caratteristiche / for the meaning of 1 and 2 see performance curves / points 1 et 2, voir courbes de performance / Für die punkte 1-2 siehe Leistungskurve



**Оформить
Заказ**

Ventilatorry.ru | zakaz@ventilatorry.ru | 8 (495) 133-95-09