

AFQ 4-4 poli trifase 2 velocità 400V 50 Hz
AFQ 4-4 poles 3 phase 2 speed 400 V 50 Hz

Ventilatore Fan type	Codice Code	Motore Motor type (*)		Portata (m3/h) Flow rate (m3/h) 1/2 (**)	Pot. ass.(W) W abs. 1/2 (**)	db (A) Lps at 3 m 1/2 (**)	Corrente Amp 1/2 (**)	T min/max °C
AFQ 315-35°/4-4T-A	6.801.00	110/35	alta/high	1200 / 2000	125 / 111	49.0 / 48.8	0.35 / 0.35	-30/ +70
			bassa/low	1100 / 1850	80 / 67	44.4 / 45.2	0.14 / 0.13	
AFQ 355-30°/4-4T-A	6.801.01	110/35	alta/high	1700 / 2700	156 / 130	49.5 / 49.5	0.38 / 0.36	-30/ +70
			bassa/low	1400 / 2400	100 / 81	43.4 / 45.1	0.17 / 0.14	
AFQ 400-30°/4-4T-B	6.801.02	110/50	alta/high	2500 / 3900	260 / 208	52.3 / 52.3	0.54 / 0.50	-30/ +70
			bassa/low	2100 / 3400	172 / 143	45.6 / 48.7	0.28 / 0.24	
AFQ 450-30°/4-4T-B	6.801.03	135/50	alta/high	3600 / 6000	460 / 330	56.5 / 57.7	0.88 / 0.74	-30/ +70
			bassa/low	2900 / 5000	290 / 240	51.2 / 53.6	0.48 / 0.39	
AFQ 500-30°/4-4T-B	6.801.04	135/70	alta/high	4700 / 8100	720 / 560	61.5 / 61.3	1.36 / 1.16	-30/ +60
			bassa/low	3650 / 6400	440 / 390	55.3 / 57.1	0.75 / 0.63	
AFQ 560-30°/4-4T-B	6.801.05	135/90	alta/high	6700 / 10900	1030 / 780	62.3 / 63.3	1.83 / 1.47	-30/ +70
			bassa/low	4100 / 8800	620 / 557	56.7 / 57.3	1.05 / 0.87	
AFQ 630-25°/4-4T-B	6.801.06	135/90	alta/high	8500 / 13900	1230 / 900	67.3 / 62.0	2.13 / 1.73	-30/ +40
			bassa/low	6100 / 11600	850 / 690	60.2 / 58.1	1.35 / 1.10	

AFQ 6-6 poli trifase 2 velocità 400V 50 Hz
AFQ 6-6 poles 3 phase 2 speed 400 V 50 Hz

Ventilatore Fan type	Codice Code	Motore Motor type (*)		Portata (m3/h) Flow rate (m3/h) 1/2 (**)	Pot. ass.(W) W abs. 1/2 (**)	db (A) Lps at 3 m 1/2 (**)	Corrente Amp 1/2 (**)	T min/max °C
AFQ 315-35°/6-6T-A	6.801.10	110/35	alta/high	800 / 1300	66 / 61	37.6 / 37.6	0.23 / 0.22	-30/ +70
			bassa/low	650 / 1200	36 / 31	35.4 / 35.4	0.08 / 0.08	
AFQ 355-30°/6-6T-A	6.801.11	110/35	alta/high	1150 / 1850	79 / 68	41.0 / 40.5	0.25 / 0.24	-30/ +70
			bassa/low	1000 / 1650	42 / 37	38.4 / 38.3	0.09 / 0.08	
AFQ 400-30°/6-6T-B	6.801.12	110/35	alta/high	1500 / 2500	100 / 84	41.1 / 42.4	0.24 / 0.23	-30/ +70
			bassa/low	1200 / 2200	56 / 48	36.1 / 39.2	0.10 / 0.09	
AFQ 450-30°/6-6T-B	6.801.13	135/50	alta/high	2600 / 4200	210 / 178	48.6 / 50.2	0.64 / 0.61	-30/ +70
			bassa/low	2100 / 3700	125 / 106	43.9 / 46.7	0.25 / 0.21	
AFQ 500-30°/6-6T-B	6.801.14	135/50	alta/high	3400 / 5500	270 / 220	49.5 / 52.3	0.66 / 0.61	-30/ +70
			bassa/low	2700 / 4600	153 / 135	42.5 / 47.0	0.29 / 0.27	
AFQ 560-30°/6-6T-B	6.801.15	135/70	alta/high	4500 / 7500	390 / 310	51.0 / 53.8	0.95 / 0.88	-30/ +70
			bassa/low	3800 / 6100	230 / 204	44.8 / 50.1	0.44 / 0.39	
AFQ 630-30°/6-6T-B	6.801.16	135/70	alta/high	5500 / 9900	530 / 460	54.8 / 54.5	1.1 / 0.9	-30/ +50
			bassa/low	3800 / 7400	270 / 260	43.6 / 47.4	0.5 / 0.45	

(*) vedi tabelle dimensioni / see dimensional sheet / voir table des dimensions / siehe Maßblatt

(**) per i punti 1 e 2 vedi curve caratteristiche / for the meaning of 1 and 2 see performance curves / points 1 et 2, voir courbes de performance / Für die punkte 1-2 siehe Leistungskurve



**Оформить
Заказ**

Ventilatorry.ru | zakaz@ventilatorry.ru | 8 (495) 133-95-09