


RLE E1-/E3-/E6-
4045-EC-05/M5

THE EVOLUTION
CONTINUES.
RLE^{EVO}


Performance charts



$\rho_1 = 1.20 \text{ kg/m}^3$

Performance curves and sound data are valid only for the motor impeller in connection with our inlet cone!

Measured in installation A according to ISO 5801:



$L_{WA6} = L_{WA5} + \Delta L_{WA}$	
RLE E_-	4045
ΔL_{WA}	+4 dB

Sounds

The value for the discharge side L_{WA6} can be calculated with the following formula.

Inlet side

$L_{Wfc5} = L_{WA5} + L_{Wrel5}$

Relative sound power level for inlet side L_{Wrel5} at octave centre frequencies f_c for the rated area (0.8 ... 1.3 q_{Vopt}).

RLE E_-	63	125	250	500	1000	2000	4000	8000 Hz
4045	1	4	1	-1	-8	-12	-17	-20 dB

Discharge

$L_{Wfc6} = L_{WA6} + L_{Wrel6}$

Relative sound power level for discharge side L_{Wrel6} at octave centre frequencies f_c for the rated area (0.8 ... 1.3 q_{Vopt}).

RLE E_-	63	125	250	500	1000	2000	4000	8000 Hz
4045	-5	-5	-4	-4	-4	-8	-13	-19 dB



Оформить
Заказ

RLE E1-/E3-/E6-4045-EC-05/M5

THE EVOLUTION
CONTINUES.
RLE^{EVO}

Technical Data

Fan type	Max. power consumption	Voltage/ connection	Frequency	max. speed	L_{WA5} at Q_{Vopt} (N_{max})	Nominal current	Protection/ temp. class	Calibration factor	media temp.
RLE E1-/E3-/E6-	kW	V	Hz	1/min	dB	A		m ² s/h	°C
RLE ...-4045-EC-05/M5	1.50	380...480, 3~	50/60	1880	80	2.5*	IP54/F	155	-20...+40


L_{WA6} = A-weighted sound power level at discharge

* at a voltage of 400 V



Dimensions in mm, subject to change.




RLE E1-4045-EC-05/M5 20 kg



RLE E3-4045-EC-05/M5 26 kg



RLE E6-4045-EC-05/M5 28 kg




Оформить
Заказ

Ventilatorry.ru | zakaz@ventilatorry.ru | 8 (495) 133-95-09

RLE E1-/E3-/E6-
4045-EC-06/M6

THE EVOLUTION
CONTINUES.
RLE^{EVO}


Performance charts



$\rho_1=1.20 \text{ kg/m}^3$

Performance curves and sound data are valid only for the motor impeller in connection with our inlet cone!

Measured in installation A according to ISO 5801:



$L_{WA6} = L_{WA5} + \Delta L_{WA}$	
RLE E_-	4045
ΔL_{WA}	+4 dB

Sounds

The value for the discharge side L_{WA6} can be calculated with the following formula.

Inlet side

$L_{Wfc5} = L_{WA5} + L_{Wrel5}$

Relative sound power level for inlet side L_{Wrel5} at octave centre frequencies f_c for the rated area (0.8 ... 1.3 q_{Vopt}).

RLE E_-	63	125	250	500	1000	2000	4000	8000 Hz
4045	1	4	1	-1	-8	-12	-17	-20 dB

Discharge

$L_{Wfc6} = L_{WA6} + L_{Wrel6}$

Relative sound power level for discharge side L_{Wrel6} at octave centre frequencies f_c for the rated area (0.8 ... 1.3 q_{Vopt}).

RLE E_-	63	125	250	500	1000	2000	4000	8000 Hz
4045	-5	-5	-4	-4	-4	-8	-13	-19 dB



Оформить
Заказ

RLE E1-/E3-/E6-4045-EC-06/M6

THE EVOLUTION
CONTINUES.
RLE^{EVO}

Technical Data

Fan type	Max. power consumption	Voltage/ connection	Frequency	max. speed	L_{WA5} at Q_{Vopt} (N_{max})	Nominal current	Protection/ temp. class	Calibration factor	media temp.
RLE E1-/E3-/E6-	kW	V	Hz	1/min	dB	A		m²s/h	°C
RLE ...-4045-EC-06/M6	2.70	380...480, 3~	50/60	2270	85	4.2*	IP54/F	154	-20...+40


L_{WA6} = A-weighted sound power level at discharge

* at a voltage of 400 V



Dimensions in mm, subject to change.




RLE E1-4045-EC-06/M6 27 kg



RLE E3-4045-EC-06/M6 38 kg



RLE E6-4045-EC-06/M6 38 kg



Оформить
Заказ

Ventilatorry.ru | zakaz@ventilatorry.ru | 8 (495) 133-95-09