

Technical Data

Impeller Data

Impeller diameter	D_r	288	mm
Number of blades	z	11	
Moment of Inertia	J	0.082	kgm ²


Impeller Data

Impeller weight	m	5.7	kg
Density of media	ρ_1	1.2	kg/m ³
Tolerance class (DIN 24166)		2	

Speed limits N_{max} for ATEX execution

RZR 11/12/19	4582	1/min
--------------	-------------	-------

Performance Curves



Relative sound power level for inlet side L_{Wrel7} at octave centre frequencies f_c




Speed	Duty point	63	125	250	500	1000	2000	4000	8000	Hz
≤2653 1/min	≤0.8 q_{Vopt}	-4	2	0	-2	-5	-10	-14	-21	dB
	>0.8-1.2 q_{Vopt}	-7	0	-2	-2	-5	-9	-14	-22	dB
	>1.2-1.6 q_{Vopt}	-10	-4	-4	-2	-4	-8	-15	-24	dB
	>1.6 q_{Vopt}	-12	-7	-6	-2	-4	-8	-13	-24	dB
Speed	Duty point	63	125	250	500	1000	2000	4000	8000	Hz
>2653 1/min	≤0.8 q_{Vopt}	-7	-1	-2	-2	-4	-10	-16	-23	dB
	>0.8-1.2 q_{Vopt}	-12	-4	-5	-3	-4	-10	-15	-23	dB
	>1.2-1.6 q_{Vopt}	-14	-7	-8	-4	-4	-9	-12	-21	dB
	>1.6 q_{Vopt}	-15	-10	-11	-4	-4	-9	-12	-19	dB

Relative sound power level for discharge side L_{Wrel4} at octave centre frequencies f_c

63	125	250	500	1000	2000	4000	8000	Hz
11	8	3	-2	-8	-13	-19	-29	dB
7	5	1	-1	-7	-11	-18	-29	dB
5	3	-1	-1	-6	-9	-17	-20	dB
6	1	-2	-2	-6	-8	-14	-29	dB
63	125	250	500	1000	2000	4000	8000	Hz
8	7	2	-2	-6	-11	-19	-28	dB
4	3	-2	-4	-6	-8	-15	-26	dB
2	0	-4	-5	-6	-8	-13	-24	dB
4	0	-4	-6	-6	-8	-12	-21	dB



Оформить
Заказ

RZR _-0280**Dimensions** in mm, subject to change.**RZR 11-0280** 20 kg**RZR 12-0280** 23 kg**RZR 19-0280** 23 kg
**Оформить
Заказ**