






TEM 01-0160

TEM 08-0160

Curves

- Operation limit, see Technical Data
- do not use in this area!

Density of media **1.2 kg/m³**.Measured in installation **B** according to **ISO 5801** (ducted).

Оформить
Заказ

TEM 01-0160

TEM 08-0160

Technical Data

TEM ...	Curves	Nominal motor power kW	Poles	Motor size	Motor voltage V	Nominal frequency Hz	Connection	Nominal motor current A	Nominal motor speed 1/min	Max. media Temperature °C	Max. volume flow m³/h	Weight TEM 01/08 kg
0160-2D-08	[A1]	0.55	2	71	230/400	50	△/Y	2.35/1.36	2800	60	1270	10/13
0160-4D-05	[A2]	0.18	4	63	230/400	50	△/Y	0.97/0.56	1350	60	890	8/11

Ex II 3G c IIB T3 TEM ...	Curves	Nominal motor power kW	Poles	Motor size	Motor voltage V	Nominal frequency Hz	Connection	Nominal motor current A	Nominal motor speed 1/min	Max. media Temperature °C	Max. volume flow m³/h	Weight TEM 01/08 kg
0160-2X-08-3G	[A3]	0.55	2	71	230/400	50	△/Y	2.40/1.40	2785	60	1270	10/13
0160-4X-05-3G	[A4]	0.18	4	63	230/400	50	△/Y	1.07/0.62	1330	60	890	8/11

60 Hz TEM ...	Curves	Nominal motor power kW	Poles	Motor size	Motor voltage V	Nominal frequency Hz	Connection	Nominal motor current A	Nominal motor speed 1/min	Max. media Temperature °C	Max. volume flow m³/h	Weight TEM 01/08 kg
0160-2D-08-60	[A5]	0.63	2	71	460	60	Y	1.32	3400	60	1180	10/13
0160-4D-05-60	[A6]	0.21	4	63	460	60	Y	0.55	1650	60	1050	8/11

The given nominal motor current may not be exceeded. If the current consumption is exceeded, the volume is to be throttled correspondingly.

For fans of the ATEX execution, the guarantee for operation in explosion endangered areas or for the conveyance of explosive atmosphere expires when the motor nominal current is exceeded! For information on fans of the ATEX execution see Technical Description of this chapter.




Motor protection can take place through motor protection units with bi-metallic releases (EUM 33) or via a thermistor (NTC) temperature sensor in connection with a thermistor (NTC)-release device (EUM 03). See chapter "Accessories".

The direction of rotation is determined looking from the drive side. Anti-clockwise rotation, symbol **LG**. Clockwise rotation, symbol **RD**.











Dimensions in mm, subject to change.

TEM 01-0160

	k2
63	180
71	210
80	252
90 S	297
90 L	297
100 L	336
112 M	329
132 S	385
132 M	385



TEM 08-0160



Оформить
Заказ

Ventilatorry.ru | zakaz@ventilatorry.ru | 8 (495) 133-95-09