






产品特点

电机技术: EC 外转子
工作电压: 单相, 200-277V, 50/60Hz
电机工作制: S1 连续工作制
电机防护等级: IP54
电机绝缘等级: F
轴承: 免维护深沟球轴承
风叶材料: 冷轧钢板
风叶数量: 5
风向: 从引出线端看过去
工作环境温度: -25°C ~ +50°C
内部集成控制器, 0-10V 或 PWM 控制

Product Characteristic

Motor technology: EC Outer rotor
Supply voltage: 1~, 200-277V, 50/60Hz
Mode of Operation: S1
Protection Class: IP54
Insulation Class: F
Bearings: Maintenance-free ball bearings
Blades Material: Cold rolled sheet steel
Blades count: 5
Air direction: seen on the leads
Perm. amb. temp.: -25°C ~ +50°C
Controller Integrated, 0-10V or PWM Control



型号 Model	电压 Voltage (V)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	允许最高 环境温度 Max Environmental Temperature (°C)	重量 Weight (Kg)
ECF(K)6E300-PZA5BC0 ECF(K)6E300-PZA5SC0	230	50/60	100	0.85	2250	1600	63	50	2.8