






产品特点

电机技术: EC 外转子
 工作电压: 单相, 200-277V, 50/60Hz
 电机工作制: S1 连续工作制
 电机防护等级: IP54
 电机绝缘等级: F
 轴承: 免维护深沟球轴承
 风叶材料: 冷轧钢板
 风叶数量: 5
 风向: 从引出线端看过去
 工作环境温度: -25°C ~ +50°C
 内部集成控制器, 0-10V 或 PWM 控制

Product Characteristic

Motor technology: EC Outer rotor
 Supply voltage: 1~, 200-277V, 50/60Hz
 Mode of Operation: S1
 Protection Class: IP54
 Insulation Class: F
 Bearings: Maintenance-free ball bearings
 Blades Material: Cold rolled sheet steel
 Blades count: 5
 Air direction: seen on the leads
 Perm. amb. temp.: -25°C ~ +50°C
 Controller Integrated, 0-10V or PWM Control



型号 Model	电压 Voltage (V)	频率 Frequency (Hz)	输入功率 Input Power (W)	电流 Current (A)	风量 Air Volume (m³/h)	转速 Speed (r/min)	噪音 Noise [dB(A)]	允许最高环境温度 Max Environmental Temperature (°C)	重量 Weight (Kg)
ECF(K)6E315-PZB5BC0	230	50/60	120	0.95	2400	1800	65	50	3.1
ECF(K)6E315-PZB5SC0									