






产品特点

电机技术: EC 外转子
 工作电压: 三相, 380-480V, 50/60Hz
 电机工作制: S1 连续工作制
 电机防护等级: IP54
 电机绝缘等级: F
 轴承: 免维护深沟球轴承
 风轮材料: 镀锌钢板
 风轮旋向: 逆时针, 从引出线端看过去
 工作环境温度: -25°C ~ +50°C
 内部集成控制器, 0-10V 或 PWM 控制

Product Characteristic

Motor technology: EC Outer rotor
 Supply voltage: 3~, 380-480V, 50/60Hz
 Mode of Operation: S1
 Protection Class: IP54
 Insulation Class: F
 Bearings: Maintenance-free ball bearings
 Impeller Material: Galvanised sheet steel
 Rotation: C.C.W, seen on the leads
 Perm.amb.temp.: -25°C ~ +50°C
 Controller Integrated, 0-10V or PWM Control



型 号 Model	电 压 Voltage (V)	频 率 Frequency (Hz)	输入功率 Input Power (W)	电 流 Current (A)	风 量 Air Volume (m³/h)	转 速 Speed (r/min)	噪 音 Noise [dB(A)]	允许最高 环境温度 Max Environmental Temperature (°C)	重 量 Weight (Kg)
ECF(K)8D280-PLQDAJ0	400	50/60	1260	2.12	3700	1285	82	50	20.0