



Description

Motor technology: AC

Rated voltage U_N : 3~ 400 V (Δ/Y) ± 10 %*

Rated frequency f_N : 50 Hz* (60Hz data available)

Motor input power P_1 : 0.09/0.06 kW*

Rated current I_N : 0.23/0.11 A*

Rated speed n_N : 900/ 730 min⁻¹*

Starting current I_A : 0.51 A / 0.17 A

Current increase ΔI : 0 %

Thermal class: THCL155*

Min. permitted conveyor temperature $t_{R(min)}$: -40 °C

Max. permitted conveyor temperature $t_{R(max)}$: 70 °C

Electrical connection: Terminal box

Number of blades: 4

Protection class: IP54

Motor protection: Thermal contact

Blades: Aluminium, uncoated

Rotor: Aluminium, uncoated


Conformity: CE

ErP Data

Is not subject to the ErP Guidelines ($P_1 < 125$ W)

* Rated data

Characteristic curve



I) Measured in full bell mouth without guard grille in installation type A according to ISO 5801.

II-x) Measured in short-bell mouth with compressed side contact protection.


Connection diagram 1360-108XA Page 608

System components Page 524

Dimensions [mm]

Airflow direction V

Design K - axial bolted, mounted for short bell mouth E



		curve	U [V]	point	I [A]	power P ₁ [W]	n [min ⁻¹]	sound power level L _{WA5} [dB]
FB040-SD_2C.V4P	Δ	I	400*	②	0.23*	90*	900*	
			400	③	0.21	70	920	64
		II	400	⑤	0.21	80	920	62
	Y	III	400	⑥	0.20	70	930	62
			400	⑧	0.11	54	770	57
			400	⑨	0.09	48	820	58

*rated data

Fan ordering information

Airflow direction V

Design

K



Type

FB040-SDK.2C.V4P

Article no.

124160

Weight [kg]

5.50

Control technology

Frequency inverter
Fcontrol 3~



Page 558

Motor protection units
3~



Page 596

Transformer-based
controllers 3~



Page 591

Electronic voltage
controllers 3~



Page 578