



Description

Motor technology: AC

Rated voltage U_N : 3~ 400 V (Δ/Y) ± 10 %*

Rated frequency f_N : 50 Hz* (60Hz data available)

Motor input power P_1 : 0.15/0.10 kW*

Rated current I_N : 0.45/0.23 A*

Rated speed n_N : 920/ 730 min⁻¹*

Starting current I_A : 1.20 A / 0.36 A

Current increase ΔI : 0 %

Thermal class: THCL155*

Min. permitted conveyor temperature $t_{R(min)}$: -40 °C

Max. permitted conveyor temperature $t_{R(max)}$: 70 °C

Electrical connection: Terminal box

Number of blades: 4

Protection class: IP54

Motor protection: Thermal contact

Blades: Aluminium, uncoated

Rotor: Aluminium, uncoated

Conformity: ErP 2015, CE

ErP Data


Efficiency η_{statA} : 28.1 %

Efficiency: $N_{actual} = 40.0 / N_{target} = 40$ **

* Rated data

**ErP 2015

Characteristic curve



I) Measured in full bell mouth without guard grille in installation type A according to ISO 5801.

II-x) Measured in short-bell mouth with compressed side contact protection.


Connection diagram 1360-108XA Page 608

System components Page 524

Dimensions [mm]

Airflow direction V

Design K - axial bolted, mounted for short bell mouth E



		curve	U [V]	point	I [A]	power P ₁ [W]	n [min ⁻¹]	sound power level L _{WA5} [dB]
FB045-SD_4C.V4L	Δ	I	400*	②	0.45*	150*	920*	
			400	③	0.45	115	960	69
		II	400	⑤	0.45	130	650	63
			400	⑥	0.44	105	970	62
	Y	III	400	⑧	0.19	86	850	60
			400	⑨	0.17	65	910	61

*rated data

Fan ordering information

← Airflow direction V

Design

K



Type

FB045-SDK.4C.V4L

Article no.

124177

Weight [kg]

7.70

Control technology

Frequency inverter
Fcontrol 3~



➤ Page 558

Motor protection units
3~



➤ Page 596

Transformer-based
controllers 3~



➤ Page 591

Electronic voltage
controllers 3~



➤ Page 578