



Description

Motor technology: AC

Rated voltage U_N : 3~ 400 V (Δ/Y) $\pm 10\%$ *

Rated frequency f_N : 50 Hz* (60Hz data available)

Motor input power P_1 : 0.31/0.19 kW*

Rated current I_N : 0.72/0.39 A*

Rated speed n_N : 880/ 640 min⁻¹*

Starting current I_A : 1.80 A / 0.50 A

Current increase ΔI : 0 %

Thermal class: THCL155*

Min. permitted conveyor temperature $t_{R(min)}$: -40 °C

Max. permitted conveyor temperature $t_{R(max)}$: 70 °C

Electrical connection: Terminal box

Number of blades: 4

Protection class: IP54

Motor protection: Thermal contact

Blades: Aluminium, uncoated

Rotor: Aluminium, uncoated

Conformity: ErP 2013, CE

ErP Data


Efficiency η_{statA} : 26.2 %

Efficiency: $N_{actual} = 36.1 / N_{target} = 36^{**}$

* Rated data

**ErP 2013

Characteristic curve



I) Measured in full bell mouth without guard grille in installation type A according to ISO 5801.

II-x) Measured in short-bell mouth with compressed side contact protection.


➤ Connection diagram 1360-108XA Page 608

➤ System components Page 524

Dimensions [mm]

Airflow direction V

Design K - axial bolted, mounted for short bell mouth E



		curve	U [V]	point	I [A]	power P ₁ [W]	n [min ⁻¹]	sound power level L _{WA5} [dB]
FB050-SD_4F.V4S	Δ	I	400*	②	0.72*	310*	880*	
			400	③	0.63	230	930	73
		II	400	⑤	0.67	280	910	72
	Y	III	400	⑥	0.64	250	920	71
			400	⑧	0.38	190	700	64
			400	⑨	0.36	175	750	65

*rated data

Fan ordering information

Airflow direction V

Design

K



TypeFB050-SDK.4F.V4S

Article no.124388

Weight [kg]9.50

Control technology

Frequency inverter
Fcontrol 3~



Page 558

Motor protection units
3~



Page 596

Transformer-based
controllers 3~



Page 591

Electronic voltage
controllers 3~



Page 578