



Description

Motor technology: AC

Rated voltage U_N : 3~ 400 V (Δ/Y) ± 10 %*

Rated frequency f_N : 50 Hz* (60Hz data available)

Motor input power P_1 : 0.91/0.62 kW*

Rated current I_N : 2.00/1.10 A*

Rated speed n_N : 890/ 710 min⁻¹*

Starting current I_A : 6.10 A / 2.00 A

Current increase ΔI : 0 %

Thermal class: THCL155*

Min. permitted conveyor temperature $t_{R(min)}$: -40 °C

Max. permitted conveyor temperature $t_{R(max)}$: 70 °C

Electrical connection: Terminal box

Number of blades: 7

Protection class: IP54

Motor protection: Thermal contact

Blades: Aluminium, 1 coat paint, black

Rotor: Aluminium, 1 coat paint, black

Conformity: ErP 2015, CE

ErP Data


Efficiency η_{statA} : 37.1 %

Efficiency: $N_{actual} = 43.9 / N_{target} = 40$ **

* Rated data

**ErP 2015

Characteristic curve



Measured in full bell mouth without guard grille in installation type A according to ISO 5801.


Connection diagram 1360-108XA Page 608

System components Page 524

Dimensions [mm]



Design Q - square, full bell mouth



		curve	U [V]	point	I [A]	power P ₁ [W]	n [min ⁻¹]	sound power level L _{WA5} [dB]
FC071-SD_6K.V7	Δ	I	400*	②	2.00*	910*	890*	82
			400	③	1.75	800	900	82
	Y	II	400*	⑤	1.10*	620*	710*	76
			400	⑥	1.10	550	730	78


*rated data

Fan ordering information

Airflow direction V

Design

Q



TypeFC071-SDQ.6K.V7

Article no.123999

Weight [kg]35.70

Control technology

Frequency inverter
Fcontrol 3~

Page 558

Motor protection units
3~

Page 596

Transformer-based
controllers 3~

Page 591

Electronic voltage
controllers 3~

Page 578