

Plug fan C ATEX

ER25C

Motor ZAmotpremiumEX IE2




Description

Plug fan with high performance centrifugal impeller
Impeller made of bright sheet metal powder-coated according to resistance class 2 RAL 9005 (jet black)
Inlet nozzle with measuring device for air flow measurement
Fitting position H
Rated voltage U: 3~ 400 V
Rated frequency f: 50 Hz
Motor protection: PTC resistor
Degree of protection : IP55
Thermal class: THCL155
Min. permitted ambient temperature: -20 °C
Max. permitted ambient temperature: 40 °C
Temperature class: II 2 G c IIB T4
Conformity: EAC


Nozzle coefficients

Standard k	55
With guard grille k_g	53

Characteristic curve



Dimensions mm



C-ATEX-ZAmotpremiumEX IE2								
Rated power P_N kW	Type	Article no.	Motor size	Motor efficiency η_{mot} %	Rated current I_N A	Rated speed n_N rpm	Maximum speed n_{max} rpm	Maximum frequency f_{max} Hz
0.75	ER25C-2DY.B7.1R	130609/EX01	080M	77.4	1.67	2805	3800	67
1.1	ER25C-2DY.B7.1R	130610/EX01	080M	79.6	2.40	2835	4280	75
1.5	ER25C-2DY.D7.1R	130611/EX01	090L	81.3	3.20	2885	4700	82
2.2	ER25C-2DY.D7.1R	130612/EX01	090L	83.2	4.50	2890	5190	90

P_N kW	Type	Weight kg	T mm	T1 mm	T3 mm	T4 mm	H2 mm	Flexible inlet connector	Guard grille	Vibration damper		Frequency inverters 3~
										Spring	Rubber	
0.75	ER25C-2DY.B7.1R	35.00	452	505	370	60	440	00406430	00412699	02021196	00090144	308228
1.1	ER25C-2DY.B7.1R	35.00	452	505	370	60	440	00406430	00412699	02021196	00090144	308228
1.5	ER25C-2DY.D7.1R	45.00	452	563	370	60	445	00406430	00412699	02021196	00090144	308230
2.2	ER25C-2DY.D7.1R	45.00	452	563	370	60	445	00406430	00412699	02021197	00090144	308232

Information

ZAbuefin

Cpro

C

C ATEX

Impellers with hub

System components

Control technology

General notes