

Vpro

for single phase alternating current, 2 pole


RH25V-2E



Description

Motor technology: AC
Rated voltage U_N : 1~ 230 V*
Rated frequency f_N : 50 Hz* (60Hz data available)
Motor input power P_1 : 0.20 kW*
Rated current I_N : 0.86 A*
Rated speed n_N : 2420 min⁻¹*
Current increase ΔI : 0 %
Service capacitor C_{400V} : 6.0 μ F
Dynamic pressure: $p_{d2} = 2.9 \cdot 10^{-5} \cdot q_v^2$ [Pa]
Thermal class: **THCL155***
Min. permitted ambient temperature $t_{R(min)}$: -30 °C
Max. permitted ambient temperature $t_{R(max)}$: 60 °C
Motor protection: Thermal contact
Impeller : High Performance Composite Material, uncoated, black
* Rated data

Characteristic curve




measured with inlet ring, without guard grille according to ISO 5801

➤ Inlet ring	00407900	Page 450
➤ Connection diagram	1360-177X SW	Page 550
➤ System components		Page 448

Dimensions [mm]

Free-running motor impeller RH
in installation position H/Vu/Vo




Performance data

Type	Characteristic curve	Voltage	Operating point	Current	Motor input power	Speed	Suction side sound power level
		U [V]		I [A]	P ₁ [W]	n [min ⁻¹]	L _{WA5} [dB]
RH25V-2EP.WD.1R	I	230	①	0.54	120	2720	
		230*	②	0.86*	200*	2420*	67
		230	③	0.74	170	2550	78

*rated data

Fan ordering information

Design	RH*
Installation position	H/Vu/Vo
Electrical connection	Supply cable variable 45cm
	
Type	RH25V-2EP.WD.1R
Article no.	113237
Weight [kg]	3.10
* Inlet ring not included	

Control technology

Frequency inverter Fcontrol 1~  ➤ Page 478	Motor protection units 1~  ➤ Page 526	Transformer-based controllers 1~  ➤ Page 517	Electronic voltage controllers 1~  ➤ Page 492
---	--	---	---

Information

Cpro-ECblue

Vpro-ECblue

Vpro

L-series

M-series

System components

Control technology

General notes